



TEST REPORT



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT A902 PET
SUPPORT: FLOCK
SUBSTRATE: NONE
CERT NO.: 240208 - 0746

FMVSS 49 CFR 571 302
OEM Rev Date: Jun 22
Federal Motor Vehicle Standard Specification for Flammability of Interior Materials

TAPE REQUIREMENTS:

SECTION: Flammability
Initial, Component - Cabin Side

Specification
< 102 mm / min

Results
< B 75

Status
Pass

Initial, Component - Cabin Side

< 102 mm / min

< B 75

Pass

Initial, Component - Cabin Side

< 102 mm / min

< B 75

Pass

Initial, Component - Cabin Side

< 102 mm / min

< B 75

Pass

Initial, Component - Cabin Side

< 102 mm / min

< B 75

Pass

CERTIFIED BY:

[Signature]

David Nichols II, Automotive Lab Technician

ISSUE DATE:

1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.