TEST REPORT



250 Chester Street Painesville, Ohio 44077

Phone: 866-GO-AVERY (866-462-8379)

Fax: 888-358-4469

email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT A915
SUPPORT: FLOCK
SUBSTRATE: NONE

CERT NO.: 240201 - 1618



FMVSS 49 CFR 571 302 OEM Rev Date: Jun 22

Federal Motor Vehicle Standard Specification for Flammability of Interior Materials

TAPE REQUIREMENTS: SECTION: Flammability Initial, Component - Cabin Side	Specification < 102 mm / min	Results < B 25	Status Pass
Initial, Component - Cabin Side	< 102 mm / min	< B 25	Pass
Initial, Component - Cabin Side	< 102 mm / min	< B 25	Pass
Initial, Component - Cabin Side	< 102 mm / min	< B 25	Pass
Initial, Component - Cabin Side	< 102 mm / min	< B 25	Pass

David Nichols II, Automotive Lab Technician

CERTIFIED BY:

 $Materials \ tested \ to \ OEM \ requirements @ 72°F +/- 2°F \ and \ 50\% \ RH +/- 5\%. \ Test \ uncertainty \ and \ minor \ exclusions \ are \ available \ online \ or \ upon \ request.$

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

ISSUE DATE:

Original Test Date: 1-30-2024

1-1-25

Page 1 of 1

This laboratory is not accredited for the calibrations or tests marked *.