## **TEST REPORT**



250 Chester Street Painesville, Ohio 44077

**CERTIFIED BY:** 

866-GO-AVERY (866-462-8379) Phone:

888-358-4469 Fax:

email: psa.tape@averydennison.com URL: tapes.averydennison.com

PRODUCT: FT A915 SUPPORT: **FLOCK** PP SUBSTRATE:

240201 - 1530 CERT NO.:



FMVSS 49 CFR 571 302 OEM Rev Date: Jun 22

Federal Motor Vehicle Standard Specification for Flammability of Interior Materials

TAPE REQUIREMENTS: SECTION: Flammability Initial, Component - Cabin Side	Specification < 102 mm / min	Results < B 25	Status Pass
Initial, Component - Cabin Side	< 102 mm / min	< B 25	Pass
Initial, Component - Cabin Side	< 102 mm / min	< B 25	Pass
Initial, Component - Cabin Side	< 102 mm / min	< B 25	Pass
Initial, Component - Cabin Side	< 102 mm / min	< B 25	Pass

 $Materials \ tested \ to \ OEM \ requirements @ 72°F + /- 2°F \ and \ 50\% \ RH + /- 5\%. \ Test \ uncertainty \ and \ minor \ exclusions \ are \ available \ online \ or \ upon \ request.$ 

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes. Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.

Avery Dennison Performance Tapes 250 Chester St. Painesville, Ohio 44077

David Nichols II, Automotive Lab Technician

Original Test Date: 1-30-2024

ISSUE DATE:

Page 1 of 1

1-1-25