

888-358-4469

866-GO-AVERY (866-462-8379)

psa.tape@averydennison.com

tapes.averydennison.com

250 Chester Street

Phone:

Fax: email:

URL:

Painesville, Ohio 44077

TEST REPORT

PRODUCT: SUPPORT: SUBSTRATE: CERT NO.:

BNW 1079A FELT FE: FOIL 240131 - 0548



FMVSS 49 CFR 571 302

OEM Rev Date: Jun 22 Federal Motor Vehicle Standard Specification for Flammability of Interior Materials

TAPE REQUIREMENTS: SECTION: Flammability Initial, Component - Cabin Side	Specification < 102 mm / min	<u>Results</u> SE	<u>Status</u> Pass
Initial, Component - Cabin Side	< 102 mm / min	SE	Pass
Initial, Component - Cabin Side	< 102 mm / min	SE	Pass

CERTIFIED BY:

David Nichols II, Automotive Lab Technician

<u>1-1-25</u>

ISSUE DATE:

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request. This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes. Status opinion based upon measurements obtained by personnel with appropriate training and professional experience. This laboratory is not accredited for the calibrations or tests marked *.

Avery Dennison Performance Tapes 250 Chester St. Painesville, Ohio 44077

Original Test Date: 1-30-2024 Page 1 of 1