TEST REPORT



250 Chester Street Painesville, Ohio 44077

Phone: 866-GO-AVERY (866-462-8379)

Fax: 888-358-4469

email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: BNW 128LV
SUPPORT: FELT
SUBSTRATE: 2 MIL FOIL
CERT NO.: 240424 - 0603



FMVSS 49 CFR 571 302 OEM Rev Date: Jun 22

Federal Motor Vehicle Standard Specification for Flammability of Interior Materials

TAPE REQUIREMENTS: SECTION: Flammability Initial, Component - Cabin Side	Specification < 102 mm / min		<u>Results</u> SE/NBR	Status Pass
Initial, Component - Cabin Side	< 102 mm / min		SE/NBR	Pass
Initial, Component - Cabin Side	< 102 mm / min		SE/NBR	Pass
Initial, Component - Cabin Side	< 102 mm / min		SE/NBR	Pass
Initial, Component - Cabin Side	< 102 mm / min		SE/NBR	Pass
CERTIFIED BY:		ISSUE DATE:	<u>1-1-25</u>	

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

Original Test Date: 4-25-2024

Page 1 of 1

This laboratory is not accredited for the calibrations or tests marked *.

David Nichols II, Automotive Lab Technician