



250 Chester Street
 Painesville, Ohio 44077
 Phone: **866-GO-AVERY (866-462-8379)**
 Fax: **888-358-4469**
 email: **psa.tape@averydennison.com**
 URL: **tapes.averydennison.com**

TEST REPORT

PRODUCT: **FL 0802**
 SUPPORT: **PRODUCT**
 SUBSTRATE: **NONE**
 CERT NO.: **230104 - 1246**



FMVSS 49 CFR 571 302 S4.3

OEM Rev Date: Oct 18

Federal Motor Vehicle Standard Specification for Flammability of Interior Materials

FMVSS 49 CFR 571 302 SUMMARY TABLE:

SECTION	DESCRIPTION	REQUIREMENT	SAMPLE	RESULTS	PASS / FAIL
S4.3 (a) Flammability	Burn Rate	< 102 mm / min	1	SE	Pass
			2	SE	Pass
			3	SE	Pass

SECTION	DESCRIPTION	REQUIREMENT	SAMPLE	RESULTS	PASS / FAIL
S4.3 (b) Flammability	Burn Distance	< 51 mm / min	1	2	Pass
			2	3	Pass
			3	2	Pass

CERTIFIED BY:



Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.