



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 1158
SUPPORT: 2 MIL PET
SUBSTRATE: TEXTURED ALUMINUM
CERT NO.: 230104 - 1251

FORD ES7T4P-7G342-AA
OEM Rev Date: Jul 05
Driven Sprocket Support



III REQUIREMENTS:

Table with 5 columns: SECTION, ASTM D903, Specification, Results, Status. Contains test results for Peel Strength, Humidity Test, Thermal Cycle Test, and Fluid Immersion Test.

CERTIFIED BY:

Signature of Dave Nichols Jr.
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.