



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT B EZ
SUPPORT: EPDM FOAM
SUBSTRATE: PP
CERT NO.: 221209 - 0840

FORD ESB-M3G76-B2
OEM Rev Date: Sep 05
Tape, PET - Two Sided PSA



TAPE REQUIREMENTS:

Table with 5 columns: SECTION, Specification, Results, Status. Rows include: 3.6.1 Peel Adhesion (910.1 Pass), 3.6.2 Aged (1378.8 Pass), 3.6.3 Aged, Cycles (938.1 Pass), 3.7 Migration Stain (None NA), 3.8 Liner Removal (55 N/m Pass), 3.9 Storage Stability (No Appreciable Difference TBD).

CERTIFIED BY:

Signature of Jake Cowdrick, Automotive Application Specialist

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.