



TEST REPORT



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT B
SUPPORT: FELT
SUBSTRATE: PAINTED METAL
CERT NO.: 221209 - 0903

FORD ESB-M3G76-B2
OEM Rev Date: Sep 05
Tape, PET - Two Sided PSA

TAPE REQUIREMENTS:

Table with 5 columns: SECTION, Specification, Results, Status. Rows include: 3.6.1 Peel Adhesion (219 N/m, Pass), 3.6.2 Aged (657 N/m, Pass), 3.6.3 Aged, Cycles (438 N/m, Pass), 3.7 Migration Stain (None, NA), 3.8 Liner Removal (55 N/m, Pass), 3.9 Storage Stability (No Appreciable Difference, TBD).

CERTIFIED BY: [Signature]
Jake Cowdrick, Automotive Application Specialist

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.
This laboratory is not accredited for the calibrations or tests marked *.
Avery Dennison Performance Tapes 250 Chester St. Painesville, Ohio 44077 Original Test Date: 11-26-2014 Page 1 of 1