



TEST REPORT

PRODUCT: FT 0900X
SUPPORT: FLOCK
SUBSTRATE: ABS
CERT NO.: 240301 - 0607



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

FORD ESB M6G17-A
OEM Rev Date: Jul 12
Adhesion Requirements, PSA Antisqueak Flock

NOT FOR NEW DESIGN - NO REPLACMENT

TAPE REQUIREMENTS:

Table with 5 columns: SECTION, Specification, SAE/ASTM/ISO, Results, Status. Rows include sections 3.5 Fogging, 3.6.1 Flock Fiber, 3.6.2 Flock Adhesive, 3.6.3 Fabric, 3.6.4 Pressure Sensitive Adhesive, 3.7 Thickness, 3.8 Loose Flock, 3.9 Abrasion Resistance, 3.10 Scuffing Resistance, 3.11 Peel Adhesion, 3.12 Shear Adhesion, 3.13 RH Resistance, 3.14 Heat Resistance, 3.15 Odor, 3.16 Flammability.

CERTIFIED BY: [Signature]
David Nichols II, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.
This laboratory is not accredited for the calibrations or tests marked *.