

TEST REPORT

EXECUTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ACTM D330 Results SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ACTM D330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ACTM D330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ACTM D330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ACTM D330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ACTM D330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ACTM D330 Results Status SECTION 3.3 Peel Strength, Plastic Membrane to Panel Specification ACTM D330 Results Status SECTION 3.3 Peel Strength Plastic Membrane to Panel Specification ACTM D330 Results Status SECTION 3.4 Bond Separation Specification ACTM D330 Results Status SECTION 3.5 Cuality </th <th></th> <th></th> <th>16</th> <th>SIREFURI</th> <th></th> <th></th> <th></th>			16	SIREFURI			
 Tageweite, cois 4007 Phone: Sele-OAVERY (66-462-337) CERT NG: 221213-0756 CORD ESH-M11240-A FORD ESH-M11240-A FORD ESH-M11240-A PORD ESH-M11240-A Tegesures Sensitive Film with Biocide TAPE REQUIREMENTS: CERTING: 221213-0756 CORD ESH-M11240-A PORD ESH-M11240-A TAPE REQUIREMENTS: CERTING: 221213-0756 CORD ESH-M11240-A TAPE REQUIREMENTS: CERTING: 221213-0756 TAPE REQUIREMENTS: CERTING: 221213-0756 CORD ESH-M11240-A CERTING: 221213-0756 CERTING: 221212						ANAB	
Part Notice 22 (21 ST VOIGS 22 (21 ST VOIGS Prove: 282-20 AVEXY (985-422-2379) PORD ESH-M11P40-A Press 983-385-449 PORD ESH-M11P40-A Part Experiments PORD ESH-M11P40-A Port Rev Date: Sep 57 Adhesion Requirements Pressure Sensitive Film with Blockle Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Spacification ASTM 0330 Results Status 3.2.1, As Received 0.22 N / mm ASTM 0330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Spacification ASTM 0330 Results Status 3.2.2, Aged, Heat Aged, 7 days @ 89°C 0.22 N / mm ASTM 0330 Results Status 3.2.2, Humidity, 7 days @ 37°C / 95% RH 0.11 N / mm ASTM 0330 Results Status SECTION 3.3 Peel Strength Spacification ASTM 0330 Results Status 3.3.1, Foam to Plastic Membrane, As Received No Separation of Bond ASTM 0530 Results Status SECTION 3.4 Bond Separation Spacification ASTM 0530 Results Status 3.3.1, Foam			-				
Fax: 883-356-469 FORD ESH-M11P40-A mail: patape@avergdennison.com EVER Nev Date: Sep 87 URL: tapes.avergdennison.com Delt Mev Date: Sep 87 Adhesion Requirements Pressure Sensitive Film with Blocide TAPE REQUIREMENTS: Securifements SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification AFM 03330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification AFM 03330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification AFM 03330 Results Status SECTION 3.2 Peel Strength Plastic Membrane to Panel Specification AFM 03330 Results Status SECTION 3.3 Peel Strength Status No Baper Teaning No Baper Teaning Status 3.1, Fourn to Plastic Membrane, As Received Specification AFM 0330 Results Status SECTION 3.3 Peel Strength Specification AFM 0330 Results Status 3.1, Fourn to Plastic Membrane, As Received Specification AFM 01000 Results Results<			CERT NO.:	221213 - 0756			
mail: past.ape@gaveydemisen.com OEM Rev Date: Sep 87 VIRU: tapes.averydemisen.com Defension Requirements Pressure Sensitive Film with Blocke TAPE REQUIREMENTS: SECTION 3.2 Requirements Section 3.2 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Spacification 0.22 V rmm ASTM D333 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Spacification 0.22 V rmm ASTM D333 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Spacification 0.22 V rmm ASTM D333 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Spacification 0.11 N rm ASTM D333 Results Status SECTION 3.2 Peel Strength Status Spacification No Testion ASTM D333 Results Status SECTION 3.3 Peel Strength Status Spacification No Delamination ASTM D333 Results Status SECTION 3.4 Bond Separation No Received Spacification No Separation of Bond ASTM D1000 Results Status SECTION 3.5 Quality Spacification No Sign ASTM D						TESTING LABOR	ATORY
URI: tepes.averg/dentilison.com Addesion Requirements Pressure Sensitive Film with Bloode TAPE REQUIREMENTS: Requirements SECTION 3.2 Pool Strength, Plastic Membrane to Panel Specification 0.22 N /mm ASTM D0330 Results Status SECTION 3.2 Pool Strength, Plastic Membrane to Panel Specification 0.22 N /mm ASTM D0330 Results Status SECTION 3.2 Pool Strength, Plastic Membrane to Panel Specification 0.22 N /mm ASTM D0330 Results Status SECTION 3.2 Pool Strength, Plastic Membrane to Panel Specification 0.11 N /mm ASTM D0330 Results Status SECTION 3.2 Pool Strength 3.1, Foam to Plastic Membrane to Panel Specification No Separation ASTM D0330 Results Status SECTION 3.3 Peel Strength 3.1, Foam to Plastic Membrane to Panel Specification No Delamination ASTM D0330 Results Status SECTION 3.4 Bond Separation 3.4, 200 grant toad, 1 m (g) RT Specification No Separation of Bond ASTM D0330 Results Status S.6. Bacteria / Fungus Resistance 3.6. Bacteria / Fungus Resistance Specification Must Pass Astute No Sign Results Status S.6. Bacteria / Fungus Resistance S.6. Bacteria / Fungus Resistance Specification <b< th=""><th></th><th></th><th></th><th></th><th></th><th></th><th></th></b<>							
Control Pressure Sensitive Film with Blocked TAPE FECUREMENTS: SECTION 3.2 Requirements SECTION 3.2 Pael Strength, Plastic Membrane to Panel Specification 0.22 N mm ASTM D3330 Results Status 0.83 Status Pass SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification 0.22 N mm ASTM D3330 Results Status 0.83 Status Pass SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification 0.21 N mm ASTM D3330 Results Status Pass SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification 0.11 N mm ASTM D330 Results Status Pass SECTION 3.3 Peel Strength 2.3.1, Foam to Plastic Membrane, As Received Specification No Delamination ASTM D330 Results Foam Tearing Status Pass SECTION 3.4 Bond Separation 3.4, 200 gram load, 1 hr @ RT Specification No Separation of Bond ASTM D300 Results Results Status Pass SECTION 3.5 Quality Specification No Separation of Bond ASTM D300 Results Results Status Pass SECTION 3.6 Bacteria / Fungus Resistance 3.0, Bacteria / Fungus Resistance Specification Must Pass Astute Status Ros Tested Status Pass CERTIFIED BY: </th <th></th> <th></th> <th></th> <th>•</th> <th></th> <th></th> <th></th>				•			
TAPE RECURRENTS: SCTION 3.2 Peel Strength, Plastic Membrane to Panel Spacification 0.22 N/mm ASTM D330 Results 0.83 Status Pass SECTION 3.2 Peel Strength, Plastic Membrane to Panel Spacification 0.22 N/mm ASTM D330 Results 0.83 Status Pass SECTION 3.2 Peel Strength, Plastic Membrane to Panel Spacification 0.22 N/mm ASTM D330 Results Status 1.87 Status Pass SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification 0.11 N/mm ASTM D330 Results Status Pass SECTION 3.3 Peel Strength 3.1, Foam to Plastic Membrane, As Received Specification No Delamination ASTM D330 Results Pass Status Pass SECTION 3.4 Bond Separation 3.4, 200 gram load, 1 hr @ RT Results Status Pass Status Pass Status Pass SECTION 3.5 Quality Specification No Sign Pass ASTM D1000 Results Pass Status Pass SECTION 3.5 Bactoria / Fungus Resistance 3.6, Quality Specification Must Pass ASTM D1000 Results Pass Status Pass CERTIFIED BY Dre Wickbe Jr, Automative Lis Textindar Must Pass ISUE DATE: 11-25	URL:	tapes.averydennison.com					
3 Requirements 3.2.1, As Recoived Specification ASTM 0330 Results Status 3.2.1, As Recoived 0.22 N / mm ASTM 0330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM 0330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM 0330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM 0330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM 0330 Results Status SECTION 3.3 Peel Strength Plastic Membrane to Panel Specification ASTM 0330 Results Status SECTION 3.4 Bond Separation Specification ASTM 0330 Results Status 3.4, 200 gram load, 1 hr @ RT No Separation of Bond ASTM 01000 Results Results SECTION 3.5 Quality Specification ASTM 01000 Results Results 3.5, Quality Specification Modelly Removelo Results <td< td=""><td></td><td></td><td>Pressure Sensitive</td><td>e Fiim with biocide</td><td></td><td></td><td></td></td<>			Pressure Sensitive	e Fiim with biocide			
SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM 0330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM 0330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM 0330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM 0330 Results Status SECTION 3.2 Peel Strength Passic Membrane to Panel Specification ASTM 0330 Results Status SECTION 3.3 Peel Strength Status 0.11 N /mm ASTM 0330 Results Status SECTION 3.3 Peel Strength Specification ASTM 0330 Results Pass SECTION 3.4 Bond Separation Specification ASTM 0330 Results Status S.4, 200 gram load, 1 hr @ RT No Separation of Bond ASTM 0300 Results Status 3.5, Quality Specification ASTM 0300 Results Status 3.6, Bactoria / Fungus Resistance Specification Must Pass No Slip Pass	TAPE RE						
3.2.1, As Received 0.22 N / mm 0.83 Pass SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM D3330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel 0.22 N / mm ASTM D3330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel 0.22 N / mm ASTM D3330 Results Status SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM D3330 Results Status SECTION 3.3 Peel Strength Status 0.11 N / mm ASTM D3330 Results Status SECTION 3.4 Bond Separation No Delamination ASTM D1000 Results Pass SECTION 3.4 Bond Separation Specification ASTM D1000 Results Status S.4, 200 gram load, 1 hr @ RT No Separation of Bond ASTM D1000 Results Status SECTION 3.5 Quality Specification ASTM D1000 Results Status SECTION 3.6 Bacteria / Fungus Resistance Specification Must Pass No Slip Pass SECTION 3.6 Bacteria / Fungus Resistance Specification Must Pass Not Tested Pass SECTION 3.6 B				a 1 a 1			_
SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM D3330 Results Situlus 3.2.2, Agad, Heat Aged, 7 days @ 88°C 0.22 N / mm ASTM D3330 Results Situlus SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM D3330 Results Situlus 3.2.2, Humidity, 7 days @ 37°C / 95% RH 0.11 N / mm ASTM D3330 Results Situlus SECTION 3.3 Peol Strength Specification ASTM D3300 Results Situlus SECTION 3.4 Bond Separation Specification ASTM D3300 Results Situlus SECTION 3.4 Bond Separation No Delamination ASTM D1000 Results Situlus 3.4, 200 gram load, 1 hr @ RT No Separation of Bond ASTM D1000 Results Situlus SECTION 3.5 Quality Specification ASTM D1000 Results Situlus 3.5, Quality Specification MSTM D1000 Results Results Situlus 3.6, Bactoria / Fungus Resistance Specification Mst Pass Not Tested Pass SECTION 3.6 Bactoria / Fungus Resis		•	lembrane to Panel		ASTM D3330		
3.2.2, Aged, Heat Aged, 7 days @ 88°C 0.22 N / mm 1.87 Pass SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM D3300 Results Status 3.2.2, Humidity, 7 days @ 37°C / 95% RH 0.11 N / mm ASTM D3300 Results Status SECTION 3.3 Peel Strength Specification ASTM D3300 Results Status SECTION 3.3 Peel Strength Specification No Delamination ASTM D3300 Results Status SECTION 3.4 Bond Separation Specification No Separation of Bond ASTM D1000 Results Status 3.4, 200 gram load, 1 hr @ RT No Separation of Bond ASTM D1000 Results Status SECTION 3.5 Quality Specification ASTM D1000 Results Status SECTION 3.5 Quality Specification Mos Separation of Bond No Slip Pass SECTION 3.6 Bacteria / Fungus Resistance Specification Must Pass Not Tested Pass SECTION 3.6 Bacteria / Fungus Resistance Specification Must Pass Not Tested Pass CERTIFIED BY: Witchis J, Automotive Lab Technician ISUE DATE: 1-1-25 1-1-25	3.2.1, As	Received		0.22 N/mm		0.83	Pass
3.2.2, Aged, Heat Aged, 7 days @ 88°C 0.22 N / mm 1.87 Pass SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM D3300 Results Status 3.2.2, Humidity, 7 days @ 37°C / 95% RH 0.11 N / mm ASTM D3300 Results Status SECTION 3.3 Peel Strength Specification ASTM D3300 Results Status SECTION 3.3 Peel Strength Specification No Delamination ASTM D3300 Results Status SECTION 3.4 Bond Separation Specification No Separation of Bond ASTM D1000 Results Status 3.4, 200 gram load, 1 hr @ RT No Separation of Bond ASTM D1000 Results Status SECTION 3.5 Quality Specification ASTM D1000 Results Status SECTION 3.5 Quality Specification Mos Separation of Bond No Slip Pass SECTION 3.6 Bacteria / Fungus Resistance Specification Must Pass Not Tested Pass SECTION 3.6 Bacteria / Fungus Resistance Specification Must Pass Not Tested Pass CERTIFIED BY: Witchis J, Automotive Lab Technician ISUE DATE: 1-1-25 1-1-25							
SECTION 3.2 Peel Strength, Plastic Membrane to Panel Specification ASTM D3330 Results Status SECTION 3.3 Peel Strength 0.11 N / mm ASTM D3330 Results Status SECTION 3.3 Peel Strength Specification ASTM D3330 Results Status 3.1, Foam to Plastic Membrane, As Received No Delamination ASTM D3330 Results Status SECTION 3.4 Bond Separation Specification ASTM D1000 Results Status 3.4, 200 gram load, 1 hr @ RT No Separation of Bond ASTM D1000 Results Status SECTION 3.5 Quality Specification ASTM D1000 Results Status SECTION 3.6 Bacteria / Fungus Resistance Specification Must Pass No Tested Pass SECTION 3.6 Bacteria / Fungus Resistance Specification Must Pass No Tested Pass SECTION 3.6 Bacteria / Fungus Resistance Specification Must Pass No Tested Pass CERTIFIED BY: Dev Hickola Jr, Automotive Lia Technician ISUE DATE: 1-1-25 Landerial Status to Dev Incomerceuse			lembrane to Panel		ASTM D3330		
3.2.2, Humidity, 7 days @ 37°C / 95% RH 0.11 N / mm 1.06 Pass SECTION 3.3 Peel Strength Specification ASTM D3390 Results Status 3.3.1, Foam to Plastic Membrane, As Received No Delamination ASTM D3390 Results Status SECTION 3.4 Bond Separation Specification ASTM D1000 Results Status 3.4, 200 gram load, 1 hr @ RT No Separation of Bond ASTM D1000 Results Status SECTION 3.5 Quality Specification ASTM D1000 Results Status SECTION 3.6 Bacteria / Fungus Resistance Specification Results Status 3.6, Bacteria / Fungus Resistance Specification Must Pass Not Tested Pass CERTIFIED BY: Daw Nitchels Jr, Automotive Lab Technician ISSUE DATE: 1-1-25 Laber Status Pass	3.2.2, Ag	Jed, Heat Aged, 7 days @ 66°C		0.22 10711111		1.07	Pass
3.2.2, Humidity, 7 days @ 37°C / 95% RH 0.11 N / mm 1.06 Pass SECTION 3.3 Peel Strength Specification ASTM D3390 Results Status 3.3.1, Foam to Plastic Membrane, As Received No Delamination ASTM D3390 Results Status SECTION 3.4 Bond Separation Specification ASTM D1000 Results Status 3.4, 200 gram load, 1 hr @ RT No Separation of Bond ASTM D1000 Results Status SECTION 3.5 Quality Specification ASTM D1000 Results Status SECTION 3.6 Bacteria / Fungus Resistance Specification Results Status 3.6, Bacteria / Fungus Resistance Specification Must Pass Not Tested Pass CERTIFIED BY: Daw Nitchels Jr, Automotive Lab Technician ISSUE DATE: 1-1-25 Laber Status Pass							
3.2.2, Humidity, 7 days @ 37°C / 95% RH 0.11 N / mm 1.06 Pass SECTION 3.3 Peel Strength Specification ASTM D3390 Results Status 3.3.1, Foam to Plastic Membrane, As Received No Delamination ASTM D3390 Results Status SECTION 3.4 Bond Separation Specification ASTM D1000 Results Status 3.4, 200 gram load, 1 hr @ RT No Separation of Bond ASTM D1000 Results Status SECTION 3.5 Quality Specification ASTM D1000 Results Status SECTION 3.6 Bacteria / Fungus Resistance Specification Results Status 3.6, Bacteria / Fungus Resistance Specification Must Pass Not Tested Pass CERTIFIED BY: Daw Nitchels Jr, Automotive Lab Technician ISSUE DATE: 1-1-25 Laber Status Pass	SECTIO	N 2.2 Pool Strongth Plastic M	Iombrano to Banol	Specification		Populto	Status
SECTION 3.3 Peel Strength Specification ASTM D330 Results Status 33.1, Foam to Plastic Membrane, As Received No Delamination ASTM D330 Results Foam Tearing Pass SECTION 3.4 Bond Separation Specification ASTM D1000 Results Status 3.4, 200 gram load, 1 hr @ RT No Separation of Bond ASTM D1000 Results Status SECTION 3.5 Quality Specification ASTM D1000 Results Status SECTION 3.5 Quality Specification Results Status SECTION 3.6 Bacteria / Fungus Resistance Specification Results Status SECTION 3.6 Bacteria / Fungus Resistance Specification Not Tested Pass SECTION 3.6 Bacteria / Fungus Resistance Specification Nust Pass Not Tested Pass CERTIFIED BY: Dave Nichols Jr, Automotive Lab Technician Issue Date: 1-1-25 Labored Pass					ASTM D3550		
3.3.1, Foam to Plastic Membrane, As Received No Delamination Foam Tearing Pass SECTION 3.4 Bond Separation Specification ASTM D1000 Results Status 3.4, 200 gram load, 1 hr @ RT No Separation of Bond ASTM D1000 Results Status SECTION 3.5 Quality Specification ASTM D1000 Results Status SECTION 3.5 Quality Specification Results Status SECTION 3.6 Bacteria / Fungus Resistance Specification Results Status 3.6, Bacteria / Fungus Resistance Specification Must Pass Not Tested Pass CERTIFIED BY: Dave Nichols Jr, Automotive Lab Technician ISSUE DATE: 11-25 Leven Nichols Jr, Automotive Lab Technician	0.2.2, 110			•••••			
3.4, 200 gram load, 1 hr @ RT No Separation of Bond No Slip Pass SECTION 3.5 Quality Specification Readily Removable Results Easily Removed Status Pass SECTION 3.6 Bacteria / Fungus Resistance 3.6, Bacteria / Fungus Resistance Specification Must Pass Results Not Tested Status Pass CERTIFIED BY: Dave Hichols Jr, Automotive Lab Tachnician ISSUE DATE: 1-1-25 Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.			d		ASTM D3330		
SECTION 3.5 Quality Specification Readily Removable Results Easily Removed Status Pass SECTION 3.6 Bacteria / Fungus Resistance 3.6, Bacteria / Fungus Resistance Specification Must Pass Results Not Tested Status Pass CERTIFIED BY: Dave Nichols Jr, Automotive Lab Technician ISSUE DATE: 1-1-25					ASTM D1000		
3.5, Quality Readily Removable Easily Removed Pass SECTION 3.6 Bacteria / Fungus Resistance Specification Results Status 3.6, Bacteria / Fungus Resistance Must Pass Not Tested Pass CERTIFIED BY: Dave Nichols Jr, Automotive Lab Technician ISSUE DATE: 1-1-25 Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.							
SECTION 3.6 Bacteria / Fungus Resistance Specification Results Status 3.6, Bacteria / Fungus Resistance Must Pass Not Tested Pass CERTIFIED BY: Dave Nichols Jr, Automotive Lab Technician ISSUE DATE: 1-1-25 Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.	SECTIO	N 3.5 Quality		Specification		Results	<u>Status</u>
3.6, Bacteria / Fungus Resistance Must Pass Not Tested Pass CERTIFIED BY: Dave Nichols Jr, Automotive Lab Technician ISSUE DATE: 1-1-25 1-1-25 Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request. Pass	3.5, Qua	lity		Readily Removable		Easily Removed	Pass
3.6, Bacteria / Fungus Resistance Must Pass Not Tested Pass CERTIFIED BY: Dave Nichols Jr, Automotive Lab Technician ISSUE DATE: 1-1-25 1-1-25 Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request. Pass							
CERTIFIED BY: Discrete and Discrete a			stance				
Dave Nichols Jr, Automotive Lab Technician Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.	3.6, Bact	teria / Fungus Resistance		Must Pass		Not lested	Pass
Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.	CERTIF		M	IS	SUE DATE:	1-1-25	
		Dave Nichols Jr, Automotive Lab	lechniclan				
				-			est.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes. Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.

Avery Dennison Performance Tapes 250 Chester St. Painesville, Ohio 44077