



250 Chester Street  
 Painesville, Ohio 44077  
 Phone: 866-GO-AVERY (866-462-8379)  
 Fax: 888-358-4469  
 email: psa.tape@averydennison.com  
 URL: tapes.averydennison.com

**TEST REPORT**

PRODUCT: FT 1126 12 PT BD  
 SUPPORT: 1 MM FELT  
 SUBSTRATE: ABS  
 CERT NO.: 221213 - 0851



**FORD WSS-M11P62-A**  
 OEM Rev Date: Jun 07  
 Performance Requirements for Adhesives Used in Interior Applications

**TAPE REQUIREMENTS:**

SECTION: <b>3.5</b> <b>Odor</b>	SAE J1351*	<u>Specification</u> <b>2 Rating</b>	<u>Results</u> 2 - Slight, But Noticeable Odor	<u>Status</u> <b>Pass</b>
3.5, 1 hr @ 65°C, Dry				

3.5, 1 hr @ 65°C, Wet		<b>2 Rating</b>	2 - Slight, But Noticeable Odor	<b>Pass</b>
-----------------------	--	-----------------	---------------------------------	-------------

SECTION: <b>3.4</b> <b>Flammability</b>	SAE J369	<u>Specification</u> <b>100 mm / min</b>	<u>Results</u> < B 25	<u>Status</u> <b>Pass</b>
3.4, Flammability, Initial, Component				

SECTION: <b>3.6</b> <b>Fogging</b>	SAE J1756	<u>Specification</u> <b>70 Units</b>	<u>Results</u> 98	<u>Status</u> <b>Pass</b>
3.6, 3 hrs @ 100°C, 21°C Cooling, 1 hr @ RT				

3.6, 3 hrs @ 100°C, 21°C Cooling, 16 hrs @ RT		<b>70 Units</b>	100	<b>Pass</b>
---	--	-----------------	-----	-------------

CERTIFIED BY:

  
 Jake Cowdrick, Automotive Application Specialist

ISSUE DATE:

1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.