



TEST REPORT

PRODUCT: FT 0900X PET
SUPPORT: FLOCK
SUBSTRATE: ABS
CERT NO.: 231128 - 1214



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

FORD WSS-M15P4-I
OEM Rev Date: Jul 21
Assembly Performance, Hard Mold-in-Color Interior Components
Horizontal or Vertical Parts At or Above the Belt Line
Above the Belt

TAPE REQUIREMENTS:

SECTION: 3.6 Impact Resistance
23°C Room Temperature Impact @ 610 mm

Table with 4 columns: Specification, Results, Status. Row 1: No Cracking, Breaking or Separation; Stable, No Cracks, Breaks or Lifting; Pass

SECTION: 3.10 Fogging, Method A - Photometric
3 hrs @ 100°C, 21°C Cooling, 16 hrs @ RT

Table with 4 columns: Specification, Results, Status. Row 1: 70 Units; 74.9; Pass

SECTION: 3.11 Odor
Odor, Condition 1 - 24 hrs @ RT, Deionized Water

Table with 4 columns: Specification, Results, Status. Row 1: 3 Max Rating; Not Tested; Not Tested

Odor, Condition 2 - 24 hrs @ 40°C, Deionized Water

Table with 4 columns: Specification, Results, Status. Row 1: 3 Max Rating; Not Tested; Not Tested

Odor, Condition 3 - 2 hrs @ 65°C

Table with 4 columns: Specification, Results, Status. Row 1: 3 Max Rating; Not Tested; Not Tested

SECTION: 3.12 Flammability
Initial, Component,

Table with 4 columns: Specification, Results, Status. Row 1: < 100 mm / min; < B 25; Pass

SECTION: 3.14 Determination of 90 Degree Adhesion Strength
3.14.1 Initial Adhesive Strength

Table with 4 columns: Specification, Results, Status. Row 1: 0.48 N / mm; 0.50; Pass

3.14.2 Long Term Heat Exposure - 7 Days @ 100°C

Table with 4 columns: Specification, Results, Status. Row 1: 75% of Original Value; 0.53; Pass

3.14.3 Short Term Heat, Humidity and Cold Exposure

Table with 4 columns: Specification, Results, Status. Row 1: 75% of Original Value; 0.61; Pass

SECTION: 3.14 Determination of 90 Degree Adhesion Strength
3.14.1 Initial Adhesive Strength

Table with 4 columns: Specification, Results, Status. Row 1: No Lifting or Appearance Changes; Pass


3.14.2 Long Term Heat Exposure - 7 Days @ 100°C

Table with 4 columns: Specification, Results, Status. Row 1: No Lifting or Appearance Changes; Pass

3.14.3 Short Term Heat, Humidity and Cold Exposure

Table with 4 columns: Results, Status. Multiple rows for different test conditions, all resulting in Pass.

CERTIFIED BY:



ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.