



250 Chester Street
 Painesville, Ohio 44077
 Phone: **866-GO-AVERY (866-462-8379)**
 Fax: **888-358-4469**
 email: **psa.tape@averydennison.com**
 URL: **tapes.averydennison.com**

TEST REPORT

PRODUCT: **FT 0900X**
 SUPPORT: **FLOCK**
 SUBSTRATE: **SS**
 STD CERT NO.: **231204 - 0816**



GM 9985281
 OEM Rev Date: Sep 15
 Adhesive, Film
 Table 1: Material Properties as Received
 Low Temperature

Table 1: Material Properties as Received

3 Requirements

SECTION: **Mass**

Product Less Liner

| <u>Specification</u> | <u>Results</u> | <u>Status</u> |
|---|----------------|---------------|
| > 0.06 < 0.20 kg/m² | 0.13 | Pass |

SECTION: **Solids Content**

Solids, 45 mins @ 105°C

| <u>Specification</u> | <u>Results</u> | <u>Status</u> |
|----------------------|----------------|---------------|
| 94.5 % min | 99.7 | Pass |

SECTION: **Thickness of Adhesive**

0.09 to 1.75 mm (.004 to .065 in)

TAPPI 411

| <u>Specification</u> | <u>Results</u> | <u>Status</u> |
|---------------------------------|----------------|---------------|
| > 0.090 < 1.650 mm | 0.157 | Pass |

SECTION: **Peel Adhesion**

Table 1, Initial, Room Temp

ASTM D3330

| <u>Specification</u> | <u>Results</u> | <u>Status</u> |
|----------------------|----------------|---------------|
| 535 N / m | 896.4 | Pass |

SECTION: **Holding Power**

Table 1, Low Temp, 1000g @ 23°C, PET Support

ASTM D3564 Method A

| <u>Specification</u> | <u>Results</u> | <u>Status</u> |
|----------------------|----------------|---------------|
| > 25 mins | 126.2 | Pass |

SECTION: **Liner Removal**

Table 1, Initial, Room Temp

ASTM D3330

| <u>Specification</u> | <u>Results</u> | <u>Status</u> |
|----------------------|----------------|---------------|
| < 45 N / m | 13.9 | Pass |

CERTIFIED BY:



Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.