



250 Chester Street  
Painesville, Ohio 44077  
Phone: 866-GO-AVERY (866-462-8379)  
Fax: 888-358-4469  
email: psa.tape@averydennison.com  
URL: tapes.averydennison.com

## TEST REPORT

PRODUCT: FT 0401  
SUPPORT: PRODUCT  
SUBSTRATE: ALUMINUM  
CERT NO.: 251008 - 1322



GMW 16865 TYPE-II-GRADE A  
OEM Rev Date: Dec 17  
Protective Tapes

This grade is used for the protection of molded or extruded interior plastic parts from the supplier to the assembly plant and is to be removed by the dealer

### TAPE REQUIREMENTS:

SECTION: **Shrink**  
24 hrs @ 85°C

Specification  
1 mm

Results  
0.0

Status  
Not Applicable

SECTION: **Shipping and Storage Stability**  
Storage Stability Cycle  
17 hrs @ -30°C  
7 hrs @ 23°C  
72 hrs @ 54°C

Specification  
No Lifting or Loss of Adhesion

Results  
Not Applicable

Status  
Not Applicable

SECTION: **Abrasion**  
GMW3208, No Weight, CS-10 Wheels, 50 Cycles

Specification  
No Wear Thru to Substrate

Results  
Not Applicable

Status  
Not Applicable

SECTION: **Edge Adhesion and Removal**  
Not Applicable

Specification  
Not Applicable

Results  
Not Applicable

Status  
Not Applicable

SECTION: **As Received**  
24 hrs @ RT

Specification  
No Adhesive Transfer,  
Degradation, Tearing or

Results  
No Adhesive Transfer,  
Degradation, Tearing or Removal

Status  
Pass

SECTION: **Exterior Oven Aged**  
Not Applicable

Specification  
No Adhesive Transfer,  
Degradation, Tearing or

Results  
Not Applicable

Status  
Not Applicable

SECTION: **Interior Oven Aged**  
Not Applicable

Specification  
No Adhesive Transfer,  
Degradation, Tearing or

Results  
No Adhesive Transfer,  
Degradation, Tearing or Removal

Status  
Pass

SECTION: **After 2 Cycles GMW 14124 Cycle M**  
GMW 14124 12, 2x Cycle M 23 hrs @ 38°C / 100% RH  
1 hr @ RT  
18 hrs @ 95°C  
1 hr @ RT  
4 hrs @ -30°C  
1 hr @ RT

Specification  
No Adhesive Transfer,  
Degradation, Tearing or

Results  
No Adhesive Transfer,  
Degradation, Tearing or Removal

Status  
Pass

SECTION: **Humidity**  
Not Applicable

Specification  
No Adhesive Transfer,  
Degradation, Tearing or

Results  
Not Applicable

Status  
Not Applicable

SECTION: **Interior Xenon**  
GMW 14162 Cycle D, 112 kj/m<sup>2</sup>

Specification  
No Adhesive Transfer,  
Degradation, Tearing or

Results  
Not Applicable

Status  
Not Applicable

SECTION: **Xenon Exterior Exposure**  
Not Applicable

Specification  
No Adhesive Transfer,  
Degradation, Tearing or

Results  
Not Applicable

Status  
Not Applicable

SECTION: **Cold Flexibility**  
Not Applicable

Specification  
No Cracking of Film

Results  
Not Applicable

Status  
Not Applicable

CERTIFIED BY:

David Nichols II, Automotive Lab Technician

ISSUE DATE:

1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.