



250 Chester Street  
Painesville, Ohio 44077  
Phone: 866-GO-AVERY (866-462-8379)  
Fax: 888-358-4469  
email: psa.tape@averydennison.com  
URL: tapes.averydennison.com

**TEST REPORT**

PRODUCT: FT A902 PET  
SUPPORT: FLOCK  
SUBSTRATE: ABS  
STD CERT NO.: 230922 - 0607



**GMW 16875 TYPE II-CYCLE-D**

OEM Rev Date: Oct 18

Performance Requirements of Anti-Squeak, Itch, Rattle Fiber Tape  
Type II material is a nonwoven tape coated with a permanent acrylic PSA  
Initial

**TAPE REQUIREMENTS:**

SECTION:	Standard	Specification	Results	Status
Initial RT	ISO 8510-2	900 N / m	19.3	Pass
SECTION: <b>Peel Adhesion</b> Aged, 72 hrs @ RT	ISO 8510-2	280 N / m	1264.2	Pass
Humidity, 24 hrs @ 38°C / 95% RH		280 N / m	1516.9	Pass
Aged, 168 hrs @ 70°C		280 N / m	1303.9	Pass
GMW 14124 CYCLE D		280 N / m	1376.9	Pass
24 hrs @ 38°C / 100% RH				
4 hrs @ 85°C				
3 hrs @ RT				
17 hrs @ 85°C				
168 hrs @ 70°C				
4 hrs @ -30C				
100 hrs @ 70°C				
SECTION: <b>Shear Strength, MD</b> 4 hrs @ -18°C	ASTM D1000	2500 N / m	15744.4	Pass
24 hrs @ 60°C		2500 N / m	11910.9	Pass
SECTION: <b>Taber Abrasion*</b> 500 Cycles CS-10,0.5 kg Load	GMW3208	No Wear Thru to Fabric Backing	Worn But Not Thru	Pass
SECTION: <b>Flammability</b> Initial, Component	GMW3232	100 mm / min	< B 25	Pass
SECTION: <b>Xenon Weatherometer*</b> Not Applicable	GMW14162	No Degradation, Stiffening, Bleaching or Objectionable Color	Not Applicable	NA
SECTION: <b>Odor*</b> Wet Condition, Coding A - 24 hrs @ 70°C, Deionized Water Dry Condition, Coding B - 24 hrs @ 70°C High Temp Condition - 24 hrs @ 105°C	GMW3205	6 Min Rating	Not Tested Not Tested Not Tested	NT NT NT
SECTION: <b>VOC*</b> Per GMW 16853	GMW15634	6 mg	Not Tested	Not Tested
SECTION: <b>Gravimetric Fogging</b> 18 hrs @ 100°C, 21°C Cooling, 24 hr RT Desiccant	GMW3235 Method B	< 2 mg	1.40000	Pass

CERTIFIED BY:



ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.