

250 Chester Street Painesville, Ohio 44077

Phone: 866-GO-AVERY (866-462-8379)

Fax: 888-358-4469

email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: UHMW 527

SUPPORT: POLYETHYLENE

SUBSTRATE: ABS

STD CERT NO.: 240717 - 0756



GMW 16875 TYPE II-CYCLE-D

OEM Rev Date: Oct 18

Performance Requirements of Anti-Squeak, Itch, Rattle Fiber Tape Type II material is a nonwoven tape coated with a permanent acrylic PSA

TEST REPORT

Initial

TAPE RI	EQUIREN	VIENTS:
---------	---------	---------

SECTION: Liner Removal Initial RT	ISO 8510-2	Specification 900 N/m	Results 5.7	Status Pass
SECTION: Peel Adhesion Aged, 72 hrs @ RT	ISO 8510-2	Specification 280 N/m	<u>Results</u> 1050.9	Status Pass
Humidity, 24 hrs @ 38°C / 95% RH		280 N/m	1309.6	Pass
Aged, 168 hrs @ 70°C		280 N/m	1608.2	Pass
GMW 14124 CYCLE D 24 hrs @ 38°C / 4 hrs @ 85°C 3 hrs @ RT 17 hrs @ 85°C 168 hrs @ 70°C 4 hrs @ -30C	100% RH	280 N/m	1600.5	Pass

SECTION: Shear Strength, MD	ASTM D1000	Specification	<u>Results</u>	Status
4 hrs @ -18°C		2500 N / m	4250.8	Pass
24 hrs @ 60°C		2500 N/m	3767.5	Pass
SECTION: Taber Abrasion*	GMW3208	Specification	<u>Results</u>	<u>Status</u>
500 Cycles CS-10,0.5 kg Load		No Wear Thru to Fabric Backing	Not Tested	Not Tested
SECTION: Flammability	GMW3232	Specification	<u>Results</u>	Status
Initial, Component		100 mm / min	< B 25	Pass
SECTION: Xenon Weatherometer* Not Applicable	GMW14162	Specification No Degradation, Stiffening, Bleaching or Objectionable Color	Results Not Applicable	Status NA

SECTION: Odor*	GMW3205	<u>Specification</u>	<u>Results</u>	Status
Wet Condition, Coding A - 24 hrs @ 70	0°C, Deionized Water	6 Min Rating	Not Tested	Not Tested
Dry Condition, Coding B - 24 hrs @ 70	°C		Not Tested	Not Tested
High Temp Condition - 24 hrs @ 105%			Not Tested	Not Tested

SECTION: VOC*	GMW15634	<u>Specification</u>	<u>Results</u>	<u>Status</u>
Per GMW 16853		6 mg	Not Tested	NA

SECTION: Gravimetric Fogging GMW3235 Method B Specification Results 18 hrs @ 100°C, 21°C Cooling, 24 hr RT Desiccant Specification 0.1 Pass

CERTIFIED BY:

David Nichols II. Automotive Lab Technician

100 hrs @ 70°C

ISSUE DATE: <u>1-1-25</u>

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.