



TEST REPORT



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 8217
SUPPORT: 1 MM FELT
SUBSTRATE: PP
STD CERT NO.: 240930 - 0733

GMW 3232
OEM Rev Date: Mar 20
Test Method for Determining the Flammability of Interior Trim Materials

TAPE REQUIREMENTS:

Table with 7 columns: SECTION, Specification, Bmax, BStat, Results, Status. Row 1: SECTION: 4.1 Flammability, FMVSS 302, Specification < 100 mm / min, Bmax 11.5, BStat 10.1, Results < B 25, Status Pass.

Table with 7 columns: SECTION, Specification, Bmax, BStat, Results, Status. Row 1: SECTION: 4.1.1, Component, CD (Lateral) Tape - Initial, As Received, Specification < 100 mm / min, Bmax 11.7, BStat 10.8, Results < B 25, Status Pass.

CERTIFIED BY:

Signature of David Nichols II
David Nichols II, Automotive Lab Technician

ISSUE DATE: JE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.