



250 Chester Street  
 Painesville, Ohio 44077  
 Phone: **866-GO-AVERY (866-462-8379)**  
 Fax: **888-358-4469**  
 email: **psa.tape@averydennison.com**  
 URL: **tapes.averydennison.com**

**TEST REPORT**

PRODUCT: **FT 2018**  
 SUPPORT: **OPEN**  
 SUBSTRATE: **FOIL**  
 CERT NO.: **221216 - 0957**



**GMW 3235 Method A**  
 Test Method Rev Date: 2011  
 Fogging Characteristics of Trim Materials

**TAPE REQUIREMENTS:**

SECTION: **Fogging** GMW3235, Method A 11  
 FT 2018 6 hrs @ 85°C, 38°C Cooling, 1 hr @ RT

**Specification**  
**60 Units**

**Results**  
 98

**Status**  
**Pass**


FT 2018 6 hrs @ 85°C, 38°C Cooling, 16 hrs @ RT

**60 Units**

97

**Pass**

CERTIFIED BY:



Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.