



250 Chester Street
 Painesville, Ohio 44077
 Phone: **866-GO-AVERY (866-462-8379)**
 Fax: **888-358-4469**
 email: **psa.tape@averydennison.com**
 URL: **tapes.averydennison.com**

TEST REPORT

PRODUCT: **FT 7770**
 SUPPORT: **OPEN**
 SUBSTRATE: **FOIL**
 CERT NO.: **221216 - 0957**



GMW 3235 Method A
 Test Method Rev Date: 2011
 Fogging Characteristics of Trim Materials

TAPE REQUIREMENTS:

SECTION: **Fogging** GMW3235, Method A 11
 FT 7770 6 hrs @ 85°C, 38°C Cooling, 1 hr @ RT

Specification
60 Units

Results
 100

Status
Pass


FT 7770 6 hrs @ 85°C, 38°C Cooling, 16 hrs @ RT

60 Units

99

Pass

CERTIFIED BY:



Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: **1-1-25**

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.