



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 7951
SUPPORT: OPEN
SUBSTRATE: FOIL
CERT NO.: 221216 - 0957



GMW 3235 Method A
Test Method Rev Date: 2011
Fogging Characteristics of Trim Materials

TAPE REQUIREMENTS:

SECTION: Fogging GMW3235, Method A 11
FT 7951 6 hrs @ 85°C, 38°C Cooling, 1 hr @ RT

Specification
60 Units

Results
100

Status
Pass

FT 7951 6 hrs @ 85°C, 38°C Cooling, 16 hrs @ RT

60 Units

99

Pass

CERTIFIED BY:

[Signature]
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.