



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 8392
SUPPORT: FOAM
SUBSTRATE: FOIL
CERT NO.: 221222 - 0738



TOYOTA TSM-0503G
OEM Rev Date: Dec 06
Fogging Test method for Non-Metallic Materials
Method B
Below the Belt Line

TAPE REQUIREMENTS:

3.2 Accelerated Fogging Test SAE J1756

SECTION: 3.2.2 Method B

3.2.2, 3 hrs @ 70°C, 21°C Cooling, 16 hrs @ RT

Specification
85 % Minimum

Results
99.3

Status
Pass

CERTIFIED BY:

[Signature]
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.