

# TEST REPORT

250 Chester Street  
Painesville, Ohio 44077  
Phone: **866-GO-AVERY (866-462-8379)**  
Fax: **888-358-4469**  
email: **psa.tape@averydennison.com**  
URL: **tapes.averydennison.com**

PRODUCT: **Fasson 0808**  
SUPPORT: **FOIL**  
SUBSTRATE: **ABS**  
CERT NO.: 230901 - 0827

**VOLVO VCS 5031,19**  
OEM Rev Date: Aug 04  
**Flammability of Interior Materials**

## TAPE REQUIREMENTS:

### S4 Requirements

SECTION: <b>Flammability</b>	FMVSS 302	<u>Specification</u>	<u>Results</u>	<u>Status</u>
Initial, Component - Machine Direction, 60 sec		< 80 mm / min	DNI	Pass
Initial, Component - Cross Direction, 60 sec		< 80 mm / min	DNI	Pass
SECTION: <b>Flammability</b>		<u>Specification</u>	<u>Results</u>	<u>Status</u>
14 Days @ 70°C, Component - Machine Direction, 60 sec		< 80 mm / min	DNI	Pass
14 Days @ 70°C, Component - Cross Direction, 60 sec		< 80 mm / min	DNI	Pass
SECTION: <b>Flammability</b>		<u>Specification</u>	<u>Results</u>	<u>Status</u>
14 Days @ 38°C / 95% RH, Component - Machine Direction		< 80 mm / min	DNI	Pass
14 Days @ 38°C / 95% RH, Component - Cross Direction, 60 sec		< 80 mm / min	DNI	Pass

CERTIFIED BY:

  
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.