



TEST REPORT



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

PRODUCT: FT 0900X
SUPPORT: FLOCK
SUBSTRATE: ABS
CERT NO.: 240201 - 1441

VOLVO VCS 5031,19
OEM Rev Date: Aug 04
Flammability of Interior Materials

TAPE REQUIREMENTS:

S4 Requirements

Table with 5 columns: SECTION, FMVSS 302, Specification, Results, Status. Rows include tests for Initial, Component - Machine Direction, 60 sec and 14 Days @ 70°C, Component - Machine Direction, 60 sec.

CERTIFIED BY: [Signature]
David Nichols II, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.
This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.
Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.