

TEST REPORT

PRODUCT:	FT 0900X PET
SUPPORT:	FLOCK
SUBSTRATE:	ABS
CERT NO .:	240201 - 1441



 250 Chester Street

 Painesville, Ohio 44077

 Phone:
 866-GO-AVERY (866-462-8379)

 Fax:
 888-358-4469

 email:
 psa.tape@averydennison.com

 URL:
 tapes.averydennison.com

VOLVO VCS 5031,19 OEM Rev Date: Aug 04 Flammability of Interior Materials

TAPE REQUIREMENTS:

S4 Requirements SECTION: Flammability Initial, Component - Machine Direction, 60 sec	FMVSS 302	Specification < 80 mm / min	<u>Results</u> < B 25	<u>Status</u> Pass
Initial, Component - Cross Direction, 60 sec		< 80 mm / min	< B 25	Pass
SECTION: Flammability 14 Days @ 70°C, Component - Machine Directior	n, 60 sec	Specification < 80 mm / min	<u>Results</u> SE/NBR	<u>Status</u> Pass
14 Days @ 70°C, Component - Cross Direction, 6	60 sec	< 80 mm / min	SE/NBR	Pass
SECTION: Flammability 14 Days @ 38°C / 95% RH, Component - Machin	e Direction	Specification < 80 mm / min	<u>Results</u> SE/NBR	<u>Status</u> Pass
14 Days @ 38°C / 95% RH, Component - Cross I	Direction, 6	< 80 mm / min	SE/NBR	Pass

CERTIFIED BY:

David Nichols II, Automotive Lab Technician

ISSUE DATE:

<u>1-1-25</u>

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request. This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes. Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.

Avery Dennison Performance Tapes 250 Chester St. Painesville, Ohio 44077

Original Test Date: 1-31-2024 Page 1 of 1