



250 Chester Street  
Painesville, Ohio 44077

Phone: 866-GO-AVERY (866-462-8379)  
Fax: 888-358-4469  
email: [psa.tape@averydennison.com](mailto:psa.tape@averydennison.com)  
URL: [tapes.averydennison.com](http://tapes.averydennison.com)

## TEST REPORT

PRODUCT: FT 1159  
SUPPORT: EPDM FOAM  
SUBSTRATE: 5 MIL FOIL  
CERT NO.: 230104 - 1027



### FMVSS 49 CFR 571 302

OEM Rev Date: Jun 22

Federal Motor Vehicle Standard Specification for Flammability of Interior Materials

#### TAPE REQUIREMENTS:

SECTION: **Flammability**

Initial, Component - Cabin Side

Specification  
**< 102 mm / min**

Results  
**SE**

Status  
**Pass**

Initial, Component - Cabin Side

**< 102 mm / min**

SE

**Pass**

Initial, Component - Cabin Side

**< 102 mm / min**

SE

**Pass**

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.