



250 Chester Street  
Painesville, Ohio 44077  
Phone: 866-GO-AVERY (866-462-8379)  
Fax: 888-358-4469  
email: [psa.tape@averydennison.com](mailto:psa.tape@averydennison.com)  
URL: [tapes.averydennison.com](http://tapes.averydennison.com)

## TEST REPORT

PRODUCT: **FT 8383 EZ**  
SUPPORT: **CERAMIC FIBER**  
SUBSTRATE: **E-COATED METAL**  
CERT NO.: 230119 - 1222



**FMVSS 49 CFR 571 302**  
OEM Rev Date: Jun 22  
Federal Motor Vehicle Standard Specification for Flammability of Interior Materials

### TAPE REQUIREMENTS:

SECTION: **Flammability**  
Initial, Component - Cabin Side

Specification  
**< 102 mm / min**

Results  
DNI - Did not burn

Status  
**Pass**

Initial, Component - Cabin Side **< 102 mm / min** DNI - Did not burn **Pass**

Initial, Component - Cabin Side **< 102 mm / min** DNI - Did not burn **Pass**

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.