



250 Chester Street  
Painesville, Ohio 44077  
Phone: 866-GO-AVERY (866-462-8379)  
Fax: 888-358-4469  
email: [psa.tape@averydennison.com](mailto:psa.tape@averydennison.com)  
URL: [tapes.averydennison.com](http://tapes.averydennison.com)

## TEST REPORT

PRODUCT: BNW 5SB1K028LV  
SUPPORT: FELT  
SUBSTRATE: 2 MIL FOIL  
CERT NO.: 240508 - 0731



**FMVSS 49 CFR 571 302**  
OEM Rev Date: Jun 22  
Federal Motor Vehicle Standard Specification for Flammability of Interior Materials

### TAPE REQUIREMENTS:

SECTION: **Flammability**

Initial, Component - Cabin Side

Specification  
**< 102 mm / min**

Results  
SE/NBR

Status  
**Pass**

Initial, Component - Cabin Side

**< 102 mm / min**

SE/NBR

**Pass**

Initial, Component - Cabin Side

**< 102 mm / min**

SE/NBR

**Pass**

Initial, Component - Cabin Side

**< 102 mm / min**

SE/NBR

**Pass**

Initial, Component - Cabin Side

**< 102 mm / min**

SE/NBR

**Pass**

CERTIFIED BY:

David Nichols II, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison® Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.