



250 Chester Street  
Painesville, Ohio 44077  
Phone: 866-GO-AVERY (866-462-8379)  
Fax: 888-358-4469  
email: [psa.tape@averydennison.com](mailto:psa.tape@averydennison.com)  
URL: [tapes.averydennison.com](http://tapes.averydennison.com)

## TEST REPORT

PRODUCT: FT 8392 12 PT BD  
SUPPORT: LOW PERM FOAM  
SUBSTRATE: SS  
CERT NO.: 221213 - 0744

### FORD ESH-M11P19-B

OEM Rev Date: Mar 93

Adhesion Requirements, Cellular Rubber / Polyurethane Foam  
Pressure Sensitive Film with Biocide



#### TAPE REQUIREMENTS:

##### 3 Requirements

###### SECTION 3.1 Peel Strength

3.1.1, As Received

ASTM D3330

###### Specification

0.44 N / mm

###### Results

1.29

###### Status

Pass

###### SECTION 3.1 Peel Strength

3.1.2, Aged, Heat Aged, 7 days @ 88°C

###### Specification

0.44 N / mm

###### Results

1.61

###### Status

Pass

###### SECTION 3.1 Peel Strength

3.1.2, Humidity, 7 days @ 37°C / 95% RH

###### Specification

0.44 N / mm

###### Results

0.89

###### Status

Pass

###### SECTION 3.2 Peel Strength

3.2, Foam to Plastic Membrane, As Received

###### Specification

No Delamination

###### Results

Foam Tearing

###### Status

Pass

###### SECTION 3.3 Bond Separation

3.3, 200 gram load, 1 hr @ RT

ASTM D3330

###### Specification

No Separation of Bond

###### Results

No Slip

###### Status

Pass

###### SECTION 3.4 Quality

3.4, Quality

###### Specification

Readily Removable

###### Results

Easily Removed

###### Status

Pass

###### SECTION 3.5 Bacteria / Fungus Resistance

3.5, Bacteria / Fungus Resistance

###### Specification

Must Pass

###### Results

All Passed

###### Status

Pass

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.