



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

TEST REPORT

PRODUCT: FT 8392
SUPPORT: PET FOAM
SUBSTRATE: PAINTED METAL
CERT NO.: 221213 - 0755

FORD ESH-M11P40-A
OEM Rev Date: Sep 87
Adhesion Requirements
Pressure Sensitive Film with Biocide



TAPE REQUIREMENTS:

3 Requirements

SECTION	TEST	Specification	ASTM D903	Results	Status
3.2	Peel Strength, Plastic Membrane to Panel	0.22 N / mm			
3.2.1	As Received		ASTM D903	2.08	Pass
3.2.2	Aged, Heat Aged, 7 days @ 88°C	0.22 N / mm	ASTM D903	2.08	Pass
3.2.2	Humidity, 7 days @ 37°C / 95% RH	0.11 N / mm	ASTM D903	1.44	Pass
3.3	Peel Strength	Specification No Delamination	ASTM D903	Results Foam Tearing	Status Pass
3.3.1	Foam to Plastic Membrane, As Received				
3.4	Bond Separation	Specification No Separation of Bond		Results No Slip	Status Pass
3.4	200 gram load, 1 hr @ RT				
3.5	Quality	Specification Readily Removable		Results Easily Removed	Status Pass
3.5	Quality				
3.6	Bacteria / Fungus Resistance	Specification Must Pass		Results NGS - No Growth on Sample	Status Pass
3.6	Bacteria / Fungus Resistance				

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.