



## TEST REPORT

250 Chester Street  
Painesville, Ohio 44077  
Phone: 866-GO-AVERY (866-462-8379)  
Fax: 888-358-4469  
email: [psa.tape@averydennison.com](mailto:psa.tape@averydennison.com)  
URL: [tapes.averydennison.com](http://tapes.averydennison.com)

PRODUCT: FBD 8970 12 PT BD  
SUPPORT: LOW PERM FOAM  
SUBSTRATE: PP  
CERT NO.: 221213 - 0756

FORD ESH-M11P40-A  
OEM Rev Date: Sep 87  
Adhesion Requirements  
Pressure Sensitive Film with Biocide



### TAPE REQUIREMENTS:

#### 3 Requirements

##### SECTION 3.2 Peel Strength, Plastic Membrane to Panel

3.2.1, As Received

Specification  
0.22 N / mm

ASTM D3330

Results  
0.55

Status  
Pass

##### SECTION 3.2 Peel Strength, Plastic Membrane to Panel

3.2.2, Aged, Heat Aged, 7 days @ 88°C

Specification  
0.22 N / mm

ASTM D3330

Results  
0.78

Status  
Pass

##### SECTION 3.2 Peel Strength, Plastic Membrane to Panel

3.2.2, Humidity, 7 days @ 37°C / 95% RH

Specification  
0.11 N / mm

ASTM D3330

Results  
0.70

Status  
Pass

##### SECTION 3.3 Peel Strength

3.3.1, Foam to Plastic Membrane, As Received

Specification  
No Delamination

ASTM D3330

Results  
Foam Tearing

Status  
Pass

##### SECTION 3.4 Bond Separation

3.4, 200 gram load, 1 hr @ RT

Specification  
No Separation of Bond

ASTM D1000

Results  
No Slip

Status  
Pass

##### SECTION 3.5 Quality

3.5, Quality

Specification  
Readily Removable

Results  
Easily Removed

Status  
Pass

##### SECTION 3.6 Bacteria / Fungus Resistance

3.6, Bacteria / Fungus Resistance

Specification  
Must Pass

Results  
Not Tested

Status  
Pass

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.