



TEST REPORT

250 Chester Street
Painesville, Ohio 44077
Phone: **866-GO-AVERY (866-462-8379)**
Fax: **888-358-4469**
email: **psa.tape@averydennison.com**
URL: **tapes.averydennison.com**

PRODUCT: **FT 1126**
SUPPORT: **EPDM FOAM**
SUBSTRATE: **PAINTED METAL**
CERT NO.: **221213 - 0808**



FORD WSB M3G102-B

OEM Rev Date:

Standard Requirements for Production Materials
B - Tape, Low Density PVC Foam , Pressure Sensitive, Supersoft
Soft, Closed Cell PVC Foam Tape with One Side Adhesive
Coated And The Other Side Protected By A Coated Release

TAPE REQUIREMENTS:

SECTION:	3.12 Pressure Sensitive Adhesion	ASTM D1000	Specification	Results	Status
3.12.1, Adhesion to Stainless Steel, Initial Room Temp			440 N / m	183 * Tear	Pass

SECTION:	3.12 Pressure Sensitive Adhesion	ASTM D1000	Specification	Results	Status
3.12.2, Adhesion to Painted Metal, Initial Room Temp			440 N / m	197 * Tear	Pass

SECTION:	3.12 Pressure Sensitive Adhesive	ASTM D1000	Specification	Results	Status
3.12.3, Adhesion to Stainless Steel, Heat Resistance, 30 mins @ 120°			No Adhesion Failure	Good, Stable, No lifting or Adhesion Loss	Pass

SECTION:	3.12 Pressure Sensitive Adhesive	ASTM D1000	Specification	Results	Status
3.12.3, Adhesion to Stainless Steel, Cycling Resistance, 5X, Flat			No Adhesion Failure	Good, Stable, No lifting or Adhesion Loss	Pass
16 hrs @ 38° C / 95% RH					
4 hrs @ - 29° C					
4 hrs @ 82° C					

SECTION:	3.13 Liner Release	ASTM D1000	Specification	Results	Status
3.12 Initial Room Temp			11 N / m	7.6	Pass

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.