



250 Chester Street  
Painesville, Ohio 44077  
Phone: 866-GO-AVERY (866-462-8379)  
Fax: 888-358-4469  
email: psa.tape@averydennison.com  
URL: tapes.averydennison.com

## TEST REPORT

PRODUCT: FT 1158  
SUPPORT: EPDM FOAM  
SUBSTRATE: PAINTED METAL  
CERT NO.: 221213 - 0811

FORD WSF-M11P8-A2  
OEM Rev Date: Jan 92  
Adhesion Requirements



Sponge Rubber, High Tack

### TAPE REQUIREMENTS:

#### 3 Requirements

##### SECTION 3.3 Adhesion

3.3.1, As Received

ASTM D903

#### Specification

0.88 N / mm

#### Results

1.05

#### Status

Pass

SECTION 3.3.2 Adhesion  
3.3.2.1, Heat Aged, 14 days @ 88°C

ASTM D903

#### Specification

0.33 N / mm

#### Results

0.44

#### Status

Pass

SECTION 3.3.2 Adhesion  
3.3.2.1, Humidity, 14 days @ 37°C / 95% RH

ASTM D903

#### Specification

0.66 N / mm

#### Results

1.05

#### Status

Pass

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.