



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

TEST REPORT

PRODUCT: FT 1126 12 PT BD
SUPPORT: PORON FOAM
SUBSTRATE: PAINTED ABS
CERT NO.: 221213 - 0858

FORD WSS-M11P62-A

OEM Rev Date: Jul 05

Performance Requirements for Adhesives Used in Interior Applications
Assembly Performance Parts Below the Belt Line



TAPE REQUIREMENTS:

SECTION: 3.5 Odor	SAE J1351*	Specification	Results	Status
3.5, Odor		2 Rating	Not Tested	NT

SECTION: 3.4 Flammability	SAE J369	Specification	Results	Status
3.4, Flammability, Initial, Component		100 mm / min	B 15	Pass

SECTION: 3.6 Fogging, Oil Bath	SAE J1756	Specification	Results	Status
3.6, 3 hrs @ 100°C, 21°C Cooling, 1 hr @ RT		70 Units	95.2	Pass

3.6, 3 hrs @ 100°C, 21°C Cooling, 16 hrs @ RT	70 Units	Not Tested	NT
---	----------	------------	----

CERTIFIED BY:

Jake Cowdrick, Automotive Application Specialist

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.