



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

TEST REPORT

PRODUCT: FT 1126 12 PT BD
SUPPORT: UHMWPE
SUBSTRATE: PAINTED METAL
CERT NO.: 221213 - 0901



FORD WSS-M11P62-A

OEM Rev Date: Jul 05

Performance Requirements for Adhesives Used in Interior Applications
Assembly Performance Parts At or Above the Belt Line

TAPE REQUIREMENTS:

SECTION:	Odor	SAE J1351*	Specification	Results	Status
SECTION: 3.5	Odor	SAE J1351*	2 Rating	Not Tested	NT
3.4, Flammability, Initial, Component		SAE J369	Specification 100 mm / min	Results EBRZT	Status Pass
SECTION: 3.6	Fogging	SAE J1756	Specification 70 Units	Results 93.1	Status Pass
3.6, 3 hrs @ 100°C, 21°C Cooling, 1 hr @ RT			70 Units	97.3	Pass
3.6, 3 hrs @ 100°C, 21°C Cooling, 16 hrs @ RT					

CERTIFIED BY:

Jake Cowdrick, Automotive Application Specialist

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.