



250 Chester Street  
Painesville, Ohio 44077  
Phone: 866-GO-AVERY (866-462-8379)  
Fax: 888-358-4469  
email: [psa.tape@averydennison.com](mailto:psa.tape@averydennison.com)  
URL: [tapes.averydennison.com](http://tapes.averydennison.com)

## TEST REPORT

PRODUCT: FT 1126 12 PT BD  
SUPPORT: NITRILE VINYL FOAM  
SUBSTRATE: ABS  
STD CERT NO.: 221214 - 1418

### GMW 16443 -TYPE I

OEM Rev Date: Aug 18

Adhesion Performance Requirements For Adhesive Backed Foam

Type I - An adhesive backed foam composite that is entrapped  
and/or mechanically retained for the life of the vehicle

GMW 3221 Code A - 50% RH (+/- 5%)



### TAPE REQUIREMENTS:

#### 3.5.1 Type I Exposure

##### SECTION 3.3 Edge Adhesion

3.3, Initial, As Received

##### Specification

Securely Bonded

##### Results

Stable, No Lifting or Removal

##### Status

Pass

3.5.4, Heat Aged, ISO 188, 168 hrs @ 80C

Securely Bonded

Stable, No Lifting or Removal

Pass

3.5.5, Humidity, GMW 14729 Option A, 168 hrs @ 38°C / 100% RH

Securely Bonded

Stable, No Lifting or Removal

Pass

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request. This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Specialty Tape Division.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.