



250 Chester Street  
Painesville, Ohio 44077  
Phone: 866-GO-AVERY (866-462-8379)  
Fax: 888-358-4469  
email: psa.tape@averydennison.com  
URL: tapes.averydennison.com

## TEST REPORT

PRODUCT: FT 7700WN  
SUPPORT: PET FOAM  
SUBSTRATE: PAINTED METAL  
CERT NO.: 221215 - 1333



### GMW 16443-TYPE-I

OEM Rev Date: Dec 10

Adhesion Performance Requirements For Adhesive Backed Foam  
Type I - An adhesive backed foam composite that is entrapped and/or  
mechanically retained for the life of the vehicle

### TAPE REQUIREMENTS:

#### 3.5.1 Type I Exposure

#### SECTION 3.3 Edge Adhesion

#### 3.5.3, Initial, As Received

#### Specification

Securely Bonded

#### Results

Stable, No Lifting or Removal

#### Status

Pass

#### 3.5.4, Heat Aged, ISO 188 07, 168 hrs @ 80°C

Securely Bonded

Stable, No Lifting or Removal

Pass

#### 3.5.5, Humidity, GMW 14729 10 Option B, 168 hrs @ 40°C / 100% F

Securely Bonded

Stable, No Lifting or Removal

Pass

CERTIFIED BY:

  
Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked \*.