



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

TEST REPORT

PRODUCT: FBA 8960
SUPPORT: 5 MM XLPE FOAM
SUBSTRATES: ALUMINUM
CERT NO.: 221222 - 0743

VALEO PDT NVC 00001-C
Rev Date: Apr 11
Plastic Foam Seals - Material Specification



TEST PARAMETERS:

SECTION: Flammability Initial, Component	FMVSS 302	<u>Specification</u> < 100 mm / min	<u>Results</u> < B 25	<u>Status</u> Pass
SECTION: Odor Dry Condition - Coding B, 24 hrs @ 70°C	GMW 3205 B	<u>Specification</u> > 6 Rating	<u>Results</u> 7 Clearly Noticeable, But Not Objectionable	<u>Status</u> Pass
SECTION: Fogging, Oil Bath - Gravimetric 18 hrs @ 90°C, 21°C Cooling, Post 24 hrs @ RT	GMW 3235 Method B	<u>Specification</u> < 2 mg	<u>Results</u> 0.3	<u>Status</u> Pass
SECTION: Mildew Component, 14 days @ 40°C	GMW 3259	<u>Specification</u> No Typical Mildew Odor and or Mildew Growth	<u>Results</u> No Objectional Odor or Presence of Mildew	<u>Status</u> Pass
SECTION: Aging Test 3 Initial 48 hrs @ 23°C / 50% RH Thermal Shock - 5 Cycles 24 hrs @ -40°C 24 hrs @ 90°C / 95% RH 24 hrs @ 23°C / 50% RH		<u>Specification</u> No Adhesion Loss or Lift	<u>Results</u> Good, Stable, No Lifting Good, Stable, No Lifting Good, Stable, No Lifting	<u>Status</u> Pass Pass Pass
SECTION: Aging Test 3 Initial 48 hrs @ 23°C / 50% RH Thermal Shock - 5 Cycles 24 hrs @ -40°C 24 hrs @ 90°C / 95% RH 24 hrs @ 23°C / 50% RH 24 hrs @ 23°C / 50% RH	ISO 8510-2	<u>Specification</u> 0.2 daN/cm 0.3 daN/cm 0.3 daN/cm	<u>Results</u> 0.24 0.43 0.38	<u>Status</u> Pass Pass Pass

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE: 1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.