



250 Chester Street
Painesville, Ohio 44077
Phone: 866-GO-AVERY (866-462-8379)
Fax: 888-358-4469
email: psa.tape@averydennison.com
URL: tapes.averydennison.com

TEST REPORT

PRODUCT: FBA 8960
SUPPORT: POLYURETHANE FOAM
SUBSTRATES: ALUMINUM
CERT NO.: 221222 - 0745

VALEO PDT NVC 00001-C
Rev Date: Apr 11
Plastic Foam Seals - Material Specification



TEST PARAMETERS:

| SECTION: | TEST | Specification | Results | Status |
|---|-------------------|--------------------------|--------------------------|--------|
| SECTION: Flammability | FMVSS 302 | < 100 mm / min | SE | Pass |
| Initial, Component | | | | |
| SECTION: Odor | NVX 15 012 Rev B* | Specification | Results | Status |
| 1 hr @ 80°C, Cool to 60°C, Test | | 3 Max Rating | 1 Weak Odor | Pass |
| SECTION: Fogging, Oil Bath - Photometric | GMW 3235 Method A | Specification | Results | Status |
| 3 hrs @ 100°C, 21°C Cooling, Post 1 hr @ RT | | > 85 % | 100 | Pass |
| 3 hrs @ 100°C, 21°C Cooling, Post 16 hrs @ RT | | > 85 % | 100 | Pass |
| SECTION: Fogging, Oil Bath - Gravimetric | GMW 3235 Method B | Specification | Results | Status |
| 18 hrs @ 90°C, 21°C Cooling, 24 hr RT Desiccant | | < 4 mg | 0.63 | Pass |
| SECTION: Aging Test 3 | | Specification | Results | Status |
| Initial | | No Adhesion Loss or Lift | Good, Stable, No Lifting | Pass |
| 48 hrs @ 23°C / 50% RH | | | Good, Stable, No Lifting | Pass |
| Thermal Shock - 5 Cycles | | | Good, Stable, No Lifting | Pass |
| 24 hrs @ -40°C | | | | |
| 24 hrs @ 90°C / 95% RH | | | | |
| 24 hrs @ 23°C / 50% RH | | | | |
| SECTION: Aging Test 3 | ISO-8510-2 | Specification | Results | Status |
| Initial | | 0.2 daN/cm | 0.58 | Pass |
| 48 hrs @ 23°C / 50% RH | | 0.3 daN/cm | 0.91 | Pass |
| Thermal Shock - 5 Cycles | | 0.3 daN/cm | 1.03 | Pass |
| 24 hrs @ -40°C | | | | |
| 24 hrs @ 90°C / 95% RH | | | | |
| 24 hrs @ 23°C / 50% RH | | | | |
| 24 hrs @ 23°C / 50% RH | | | | |

CERTIFIED BY:

Dave Nichols Jr, Automotive Lab Technician

ISSUE DATE:

1-1-25

Materials tested to OEM requirements @ 72°F +/- 2°F and 50% RH +/- 5%. Test uncertainty and minor exclusions are available online or upon request.

This certificate or report shall not be reproduced except in full, without the written approval of the Avery Dennison Performance Tapes.

Status opinion based upon measurements obtained by personnel with appropriate training and professional experience.

This laboratory is not accredited for the calibrations or tests marked *.