



Avery Dennison®
Paint Protection Film warranty
and care information



Your vehicle has a
new level of protection
with Avery Dennison®
Paint Protection Film.

Using these cleaning and maintenance tips will help maintain the premium look and longevity of your Avery Dennison Paint Protection Film. Infrequent or improper maintenance can lead to premature degradation of films and lower the expected life of the film.

- Wait 48 hours after installation to wash your car.
- Remove insect or other stains as soon as possible with Avery Dennison Surface Cleaner.
- Stubborn stains can be removed with Avery Dennison Heavy Duty Cleaner or >90% Isopropyl alcohol. After using these cleaners, be sure to follow up with Avery Dennison Surface Cleaner or wash with soap and water.
- Seal with Avery Dennison Sealant at least once every 3 months to preserve finish. Waxes that are free of petroleum distillates can also be used to seal the film.
- Light scratches in the film will self-heal in 20-30 minutes at room temperature. In cooler conditions, or to accelerate the process, pour warm water (120°F) over the affected area.
- Avoid using a pressure washer or high-pressure water source near the edges of the film, it can cause the film to lift and/or become damaged.
- Surface contaminants may also be removed using a detailing clay bar or towel.

Professional Car Wash Tips

- A brushless automatic car wash with spray only is acceptable.
- Automated brush wash is not recommended as the brushes may scratch the PPF surface, catch and lift the edges of the PPF, reduce the finish and/or create a failure point.
- Skip the wax options at the car wash to avoid wax that contains petroleum distillates which can damage the PPF.
- Let the PPF dry naturally or dab dry with micro-fiber towel.

Avery Dennison PPF Warranty

Product	Warranty Period (Years)
Supreme Defense™ Gloss PPF	10
Supreme Defense™ Matte PPF	7
neo™ noir PPF	7

Avery Dennison warrants to the original film purchaser that the Avery Dennison PPF will be free from defects in manufacturing and workmanship upon shipment, and when used according to Avery Dennison's instructions, will under normal conditions provide Warranty for the period stated above, subject to the Avery Dennison Warranty Terms and Conditions.

You can install an Avery Dennison PPF film with confidence as the following defects are covered by us:

- Manufacturing & Workmanship Defects
- Cutting Defects
- Excessive film discoloration, cracking, crazing, blistering, excessive gloss changes, excessive dimensional change or loss of adhesion



Installers must register all PPF warranties online using the QR code or by accessing graphics.averydennison.com/ppfwarranty.

Extend the life of the installed PPF with our Dos and Don'ts

Do:

- Wash the film by hand, when required with a pH neutral car wash and soft cloth or sponge
- Protect your PPF with Avery Dennison Supreme Wrap Care Sealant after every wash
- Immediately spot clean bird dropping, bug splatter, tree sap and similar contaminants
- Try to park your car in shade or undercover

Do Not:

- Take your car through automated car washes. The brushes may cause the edges to lift
- Use high-pressure cleaners
- Use non-pH neutral cleaners, solvents or harsh chemicals
- Use abrasive compounds, polishes or cleaning methods
- Use paste waxes or any wax containing petroleum distillates
- Use waxes on PPF Matte

A403491 01/2025

For information on warranty terms, exclusions and certain limitations that apply please see our website: graphics.averydennison.com All statements, technical information and recommendations about Avery Dennison products are based upon tests and information believed to be reliable but do not constitute a guarantee or warranty of any kind. All Avery Dennison products are sold with the understanding that the purchaser has independently determined the suitability of such products for its intended and other purposes.

©2025 Avery Dennison Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison Corporation. Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.