Sell Sheet Europe 2025

Solutions for Warm Edge Spacers

Windows and doors






What is it and why is it used?

Warm Edge Spacers (WES) are used in Insulating Glass Units (IGU).

IGU, more commonly known as double glazing/triple glazing sealed combinations of double or triple glass window panes separated by an air/gas space to reduce heat transfer across part of the building envelope.

Energy & money saving, it reduces pollution and greatly improves the comfort inside a building! It also provides sound insulation.





Our Contribution to the Warm Edge Spacers

Avery Dennison delivers very high barrier multilayer laminates for warm edge spacer production offering exceptional water vapor and gas barrier, combined with low thermal bridge. These laminates are delivered with or without PSA.

- Ultra high barrier to moisture with market leading properties
- Negligible thermal bridge compared to Aluminum or Stainless Steel foil laminates
- Low gas permeation
- Exceptional surface treatment to enhance adhesion to sealants and spacer
- Very high resistance to corrosion

The Solutions that we Offer

	PT EU reference	Description	Advantages
PSA	XD 2527	2 ply film coated with a high grade of pure acrylic adhesive and protected with a PE coated paper liner	Excellent adhesive properties combined with good barrier properties
	XD 3827	3 ply film coated with a high grade of pure acrylic adhesive and protected with a PE coated paper liner	Excellent adhesive properties combined with good barrier properties
NON-PSA	Vapor Barrier 342A	Tri-laminate metallized PET with multisealant adhesion treatment on one side, especially to the PS high barrier sealant	Suitable for a wide range of WES, ST for maximum compatibility with a wide range of edge sealants
	Vapor Barrier 228A	Bi-laminate metallized PET with multisealant adhesion treatment	Suitable for a wide range of WES, ST for maximum compatibility with a wide range of edge sealants, low cost
	Vapor Barrier 122T	Metallized PET laminated to 6µ foil	Better thermal insulation due to lower thermal bridge compared to SS, low cost

Our technical experts are here to show you how to work with your materials successfully during every phase of your application. You can count on us to approach any challenge with genuine curiosity and care.

Contact your Avery Dennison sales representative or visit tapes.averydennison.com

Asia Pacific Kunshan, China, No. 618 Nanhe Road Kunshan Economic & Technological Zone China 215335 Phone: +86 400 6987 555 Fax: +86 512 57155059

Europe Tieblokkenlaan 1 B-2300 Turnhout Belgium Phone: +32 (0)14 40 48 11 Fax: +32 (0)14 40 48 55

North America

250 Chester Street Painesville, Ohio 44077 USA Phone: +1866-462-8379 Fax: +1888-358-4469



#MakingPossible

Please refer to tapes.averydennison.com for complete terms and conditions, including warranty terms relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

DISCLAIMER – © 2025 Avery Dennison Corporation. All rights reserved. The "Making Possible" tagline, Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are trademarks of Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. Branding and other information on any samples depicted are fictitious. Any resemblance to actual names is purely coincidental. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison. All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's general terms and conditions of sale, see terms.europe.avery dennison.com.

