




## FT 7983

### FEATURES:

- High coat-weight adhesive
- Extremely high tack adhesive
- Specially designed adhesive
- Glass fibre scrim carrier

### BENEFITS:

- Good bonding to uneven surfaces
- Provides excellent initial adhesion to a wide variety of substrates
- Ideal for bonding to foamed rubbers and plastics used in the manufacture of industrial and domestic gaskets and weather seals
- High degree of resistance to volatile components of foamed rubbers and plastics
- Dimensional stable adhesive carrier



### CONSTRUCTION:

#### Adhesive:

Permanent synthetic rubber adhesive

#### Carrier:

Glass fibre scrim

#### Liner:

Havana (yellow/brown) coloured glassine

## FT 7983

Adhesive Properties	Typical Values
<b>THICKNESS</b>	
Adhesive	144 microns
Liner MS	79 microns
Total	223 microns
*ATM.7	
<b>ADHESION 180° peel</b>	
	24 hrs
Stainless Steel	2300 N/m
Painted Steel	2150 N/m
Polypropylene	2050 N/m
Rigid polypropylene	2000 N/m
*ATM.1	
<b>SHEAR RESISTANCE</b>	
Static (1000g / 25x25mm)	6,000 mins
*ATM.14	
<b>TEMPERATURES</b>	
Application (minimum)	+ 10°C
Service (continuous)	-40°C to +80°C
Short term (30 minutes)	+95°C
*TEST METHODS	

Note: The listed values are typical only and not intended to serve as product specifications

### APPLICATION TECHNIQUES

- It is essential with all pressure-sensitive tapes the application surface is clean, dry and free of grease and oil
- Bond strength is dependent upon the amount of adhesive-to-surface contact developed
- Note that different pressure, time and temperature on different (firm / rigid) surface achieves different performance

### STORAGE AND SHELF LIFE

The shelf life of the product is two years when stored at 18-22°C / 64-72°F, 30-70% relative humidity and out of direct sunlight, in original packaging.

Please refer to [Tapes.AveryDennison.com](http://Tapes.AveryDennison.com) for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2014 Avery Dennison Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison Corporation. Avery™ and all other Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.



Performance  
Tapes

**Asia Pacific**  
Kunshan, China,  
NO. 618 Nanhe Road  
Kunshan Economic &  
Technological Zone  
China, 215335  
Phone: +86 512 57155001  
Fax: +86 512 57155059

**Europe**  
Tieblokkenlaan 1  
B-2300 Turnhout  
Belgium  
Phone: +32 (0)14 40 48 11  
Fax: +32 (0)14 40 48 55

**South America**  
Rua Francisco Foga, 225  
13280-000 Vinhedo  
SP Brazil  
Phone: +55 19 3876 7736  
Fax: +55 19 3876 7682

**North America**  
250 Chester Street  
Painesville, Ohio  
44077 USA  
Phone: +1 866-462-8379  
Fax: +1 888-358-4469

For more information on our bonding tapes and adhesive solutions, visit [Tapes.AveryDennison.com](http://Tapes.AveryDennison.com)