FASSON® 9200


FASSON® 9200 was designed as a seaming tape for vinyl faced fiberglass insulation (i.e. metal buildings).

FEATURES:

- "CT" COLD TOUGH™ Adhesive technology
- Matte Finish Vinyl

BENEFITS:

- Good quick stick properties
- Good temperature and humidity performance to work in any weather
- Plasticizer Resistant Adhesive



CONSTRUCTION:

Carrier:

Matte White Vinyl Taffeta

Adhesive:

COLD TOUGH™ Acrylic

Liner:

Densified Kraft

FASSON® 9200

Adhesive Properties:			Typical Values	
Thickness	Test Method(s): PSTC-133	US Mils	MM's	Microns (μm)
Liner:		2.5	0.06	63
Adhesive:		1.5	0.04	38
Carrier:		3.4	0.09	86
Total Caliner:		7.4	0.19	188

PEEL ADHESION	Test Method(s): PSTC-	101, ASTM D-3330, STD-10			
Product 180º 12" min					
Substrate		Lbf / In	US Oz / In	N / Meter	
SS	Initial	4.5	72	788	
 			1		
ELONGATION	Test Method(s): PSTC-	131, ASTM D-882, STD-3A,B,C			
Product 180°					
Substrate		%			
Product		135			
STATIC SHEAR	Toot Mothod(s): BSTC	107, ASTM D 3654, STD-9			
	00 g	107, ASTW D 3034, STD-9			
Substrate	50 g	Min to Fail			
SS S	Initial	> 10,000	1		
33	IIIIIai	> 10,000			
TEMPERATURES		° F	Т	° C	
Min Application Temp		0 ° F		-17 ° C	
Max Continuous Operating Temp		200 ° F		93 ° C	
Max Intermittent Operating Temp		225 ° F		107 ° C	

THE LISTED VALUES ARE TYPICAL AND NOT INTENDED TO SERVE AS PRODUCT SPECIFICATIONS

APPLICATION TECHNIQUES

- It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease or oil
- Bond strength is dependent upon the amount of adhesive-to-surface contact developed
- · Note that different pressure, time and temperature on different (film / rigid) surface achieves different performance

STORAGE / SHELF LIFE

• One year when stored at 64-72°F (18-22°C) / 30-70% relative humidity, out of direct sunlight and in original packaging.

Please refer to Tapes. Avery Dennison.com for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2015 Avery Dennison Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison Corporation. All other Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.



Performance

Asia Pacific Kunshan, China, NO. 618 Nanhe Road Kunshan Economic & Technological Zone China, 215335

Phone: +86 512 57155001 Fax: +86 512 57155059 Europe Tieblokkenlaan 1 B-2300 Turnhout Belgium Phone: +32 (0)14 40 48

Belgium Phone: +32 (0)14 40 48 11 Fax: +32 (0)14 40 48 55 North America 250 Chester Street Painesville, Ohio 44077 USA Phone: +1 866-462-8379

Phone: +1 866-462-837 Fax: +1 888-358-4469