




FT 4273

FEATURES:

- Selfwound
- Extremely high tack adhesive
- Paper carrier

BENEFITS:

- Easier conversion and handling
- Provides excellent initial adhesion to a wide variety of substrates
- Linerless construction

**CONSTRUCTION:****Carrier**

White Glassine

Adhesive:

Rubber

FT 4273

Adhesive Properties:		Typical Values		
Thickness	Test Method(s): PSTC-133	US Mils	MM's	Microns (µm)
Carrier and adhesive:		4.2	0.11	108
Total Caliper:		4.2	0.11	108

PEEL ADHESION Test Method(s): PSTC-101, ASTM D-3330, STD-10

Product 180° 12" min

Substrate		Lbf / In	US Oz / In	N / Meter
SS	20 min dwell	8.6	137	1501
Polypropylene	20 min dwell	8.6	137	1501

LOOP TACK Test Method(s): PSTC-16, STD-7

Product 180° 20" / min

Substrate		Lbf / In		
SS	Initial	9.1		

STATIC SHEAR Test Method(s): PSTC-107, ASTM D 3654, STD-9

Product 1" sq (6.5 cm2) 1000 g

Substrate		Min to Fail		
SS		> 2,000		

TEMPERATURES	° F	° C
Min Application Temp	50 ° F	10 ° C
Max Continuous Operating Temp	122 ° F	50 ° C
Max Intermittent Operating Temp	140 ° F	60 ° C

THE LISTED VALUES ARE TYPICAL AND NOT INTENDED TO SERVE AS PRODUCT SPECIFICATIONS

APPLICATION TECHNIQUES

- It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease or oil
- Bond strength is dependent upon the amount of adhesive-to-surface contact developed
- Note that different pressure, time and temperature on different (film / rigid) surface achieves different performance

STORAGE / SHELF LIFE

- Two years when stored at 64-72°F (18-22°C) / 30-70% relative humidity, out of direct sunlight and in original packaging.

Please refer to Tapes.AveryDennison.com for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2015 Avery Dennison Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison Corporation. All other Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.



Performance
Tapes

Asia Pacific
Kunshan, China,
NO. 618 Nanhe Road
Kunshan Economic &
Technological Zone
China, 215335
Phone: +86 512 57155001
Fax: +86 512 57155059

Europe
Tieblokkenlaan 1
B-2300 Turnhout
Belgium
Phone: +32 (0)14 40 48 11
Fax: +32 (0)14 40 48 55

North America
250 Chester Street
Painesville, Ohio
44077 USA
Phone: +1 866-462-8379
Fax: +1 888-358-4469