

Material Safety Data Sheet 2001/58/EC

Product name: FT7383B

1. Product and company identification

1.1. Product name: FT7383B

1.2. <u>Intended use</u>: Modified acrylic PSA tape

1.3. <u>Producer:</u> Avery Dennison Kunshan Co., Ltd.

Avery Dennison Performance Tapes

No.618 Nanhe Road Kunshan City / China

Contact person: Liyan Zhao

Product Safety Coordinator

<u>Telephone number</u>: +86 512 5715 5056

2. Composition / information on ingredients

2.1. Product Composition: Double coated pressure sensitive adhesive tape

Product code	Sub-part name	Ingredient	CAS	Content
FT7383	Adhesive	Acrylic copolymer	listed	20-70%
		Tackifier	9003-74-1	1-10%
		Others	NA	1-10%
	Carrier	PET	25038-59-9	10-40%

2.2. This product is not considered to be dangerous according to Directive 1999/45EC

2.3. <u>Hazardous components</u>

This product does not contain concentrations ≥ 1% of substances presenting a health or environmental hazard within the meaning of Directive 67/548/EEC

3. Hazard identification

There is no evidence to suggest that this material constitutes a health hazard (according to 1999/45/EC) during handling under normal safe working conditions.

4. First aid measures

Skin contact: If the skin would be irritated after prolonged contact, clean the skin

with water and soap.

Eye contact: If a part of the tape is present in the eye, treat the part as an inert

particle. Irrigate with plenty of clean water for 15 minutes; remove

contact lenses for better cleaning.

Issue date: 27/10/16 Page 1 of 4

Oral: If a piece of tape is swallowed, rinse out mouth and drink large

quantities of water. If necessary obtain medical attention.

Inhalation:

breathing difficulties.

Remove from exposure and obtain medical assistance in case of

5. Fire fighting measures

Suitable extinguishing media are foam, sand, dry powder, and carbondioxide.

Hazardous decomposition products: above the decomposition temperature the major volatiles will be carbondioxide, water carbonmonoxide and small molecular weight organic materials.

The ratio depends on the burning temperature and the presence of oxygen.

6. Accidental release measures

The product is a solid and insoluble product. Therefore uncontrolled release (into air or water) is highly unlikely.

7. Handling and storage

Handling:

Static electricity: In most processes in which there is movement of foil over metal or

other rollers, surface electrical charges develop on the film. Static charges should be eliminated or reduced as much as possible, since they provide a source of ignition for flammable vapours and gasses or may give electrical shocks to operators. Use either passive or active

static eliminators to reduce the charges.

Reeling: Machine design and work practices should be organised to remove

the danger of trapping parts of the body or clothing in reeled materials

and between the film and machinery parts.

Work area: Operators who convert the tape should work in well-ventilated areas

Storage: Store under dry conditions, out of direct sunlight and at temperatures

18-22°C.30%-70% relative humidity.

8. Exposure controls / personal protection

8.1. Exposure control:

8.1.1 Ensure sufficient ventilation.

8.1.1.1 Protective mask is not necessary in a normal ventilated work area.

8.1.1.2 Gloves are only necessary to protect hands from sharp edges of some tapes.

8.1.1.3 Eye protection (safety glasses) is only necessary in conversion operations where parts of the tape may be projected to the face.

8.1.1.4 Apply general measurements of normal hygiene.

9. Physical and chemical properties

9.1 General Information

- Physical state: the product is solid, supplied in film format and wound in rolls.

- Smell: slight resin and acrylic smell

Issue date: 27/10/16 Page 2 of 4

- Colour: Adhesive: clear. Liner: havana(yellow/brown) Carrier: transparent

9.2 Important health, safety and environmental information

pH value: not defined (solid product)
 Boiling point: not defined (solid product)
 Flashpoint: not defined (solid product)
 Decomposition temperature: not defined (solid product)
 Auto-ignition temperature: not defined (solid product)

Relative density: adhesive $1.00 \pm 0.10 \text{ gr./cm}^3$ carrier $1.4 \pm 0.10 \text{ gr./cm}^3$

Solubility in water: negligibleVapour density: NA

10. Stability / reactivity

The product is stable under normal operating conditions.

11. Toxicological information

- Inhalation: Not determined

- Skin Contact: Not determined

Cytotoxicity: Not determined

Eye contact: Not determined

- Ingestion: Not determined

- Long term exposure: This material has been in use for many years with no evidence of

adverse effects.

12. Ecological information

- Not determined
- Avoid losses to the environment whenever possible.
- Parts of the product will slowly degrade under exposure to UV-light. Adverse effects are not to be expected.

13. <u>Disposal considerations</u>

Dispose of in a safe and approved manner in accordance with local regulations.

14. Transport information

The material is <u>not</u> a hazardous good by any means for transportation.

The product does not have any restricted classification.

15. Regulatory information

According to the EG-directions, the product is <u>not</u> subject for special markings (R-sentence, S-sentence, Vbf are <u>not</u> applicable).

Issue date: 27/10/16 Page 3 of 4

16. Other information

None

This information is given in good faith and is based on our present knowledge and experience but no warranty, express or implied, is made.

For further information, please consult Avery Dennison Performance Tapes.

(+86 512 5715 5056)

Issue date: 27/10/16 Page 4 of 4