

TECHNICAL DATA SHEET

Avery Dennison™ FT 3130 is a silicone adhesive transfer tape protected with a low density polyethylene laminated liner on one side and a clear polyester on the other.

FEATURES

- Silicone adhesive
- Polyester liner

BENEFITS

- By its chemical nature outperforming on resistance towards temperature extremes, moisture, chemicals, sunlight, biological attack
- Good adhesion towards difficult to bond to surfaces
- Release system allowing easy liner removal
- Good die-cutability



CONSTRUCTION

Liner MS: Low density polyethylene laminated liner Adhesive: Silicone adhesive Liner LS: Polyester





Adhesive Properties		Typical Values		
THICKNESS (ASTM D3652)	1	US Mils	MM's	Micron's (µm)
Liner MS		5.9	0.150	150
Liner LS		1.42	0.036	36
Carrier & Adhesive		1.97	0.05	50
Total Caliper		9.29	0.236	236
PEEL ADHESION (ASTM D3330) 180° (12") 300 mm / min @ Room Temp				•
SUBSTRATE		Lbf / in	US Oz / In	N / Meter
Stainless Steel	20 min dwell			
	24 hr dwell	4.0	64	700
DYNAMIC SHEAR (ASTM D-1002) 1"sq (6.25 cm²) 2mm/min @ Room Temp				
SUBSTRATE		Lbf/in² kPa		
Stainless Steel	Initial	112.5 775		
TEMPERATURES			°F	°C
Service (continuous)			-112 °F to +482 °F	-80 °C to +250 °C
Short term (30 minutes)			+572 °F	+300 °C
Temperature shock			+1472 °F	+800 °C
	1			

Note: The listed values are typical only and not intended to serve as product specifications

APPLICATION TECHNIQUES

- It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease or oil
- Bond strength is dependent upon the amount of adhesive-to-surface contact developed
- Note that different pressure, time and temperature on different (film / rigid) surface achieves different performance

STORAGE / SHELF LIFE

Two years when stored at 64-72 °F (18-22 °C) / 30-70 % relative humidity, out of direct sunlight and in original packaging.

For more information on our bonding tapes and adhesive solutions, call us:

North America: +1 866 462 8379 Asia Pacific: +86 512 57155001 Europe: +32 (0)14 40 48 11

www.tapes.averydennison.com

@2020, Avery Dennison Corporation. Avery Dennison and the triangle logo are registered trademarks of Avery Dennison Corporation. All rights reserved.

