

TECHNICAL DATA SHEET

Avery Dennison™ FT 4351

FEATURES

- High adhesive coat-weight
- Silicone adhesive
- Very high shear resistance
- Specially treated unwind

BENEFITS

- Assures high adhesion, also on siliconized substrates
- Provides excellent resistance to chemicals
- Provides excellent splice performance, also at high temperature



CONSTRUCTION

Facestock: Transparent polyester

Adhesive: Permanent silicone adhesive - yellow

Liner: Linerless construction



Performance
Tapes

Adhesive Properties

Typical Values

THICKNESS (ASTM D3652)		US Mil's	MM's	Micron's (µm)
Adhesive & Front				75
Total Caliper				75
PEEL ADHESION (ASTM D3330)				
180° (12") 300 mm / min @ Room Temp				
SUBSTRATE		Lbf / in	US Oz / In	N / Meter
Stainless Steel	20 min dwell	2.28	37	400
siliconized Glassine Paper	20 min dwell	1.03	16	180
	24 hr dwell			
Polypropylene	20 min dwell			
	24 hr dwell			
LOOP TACK (ASTM D6195)				
(12") 300 mm / min @ Room Temp				
SUBSTRATE		Lbf / in	US Oz / In	N / Meter
Glass	Initial	4.11	65.8	720
STATIC SHEAR (ASTM D3654)				
1"sq (6.25 cm ²) 1000 g @ Room Temp				
SUBSTRATE		Min to Fail		
Stainless Steel	Initial	> 10.000		
TEMPERATURES			°F	°C
Minimum Application Temperature			32 °F	0 °C
Minimum Service Temperature			-76 °F	-60 °C
Maximum Service Temperature			392 °F	200 °C

Note: The listed values are typical only and not intended to serve as product specifications

APPLICATION TECHNIQUES

- It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease or oil
- Bond strength is dependent upon the amount of adhesive-to-surface contact developed
- Note that different pressure, time and temperature on different (film / rigid) surface achieves different performance

STORAGE / SHELF LIFE

Two years when stored at 64-72 °F (18-22 °C) / 30-70 % relative humidity, out of direct sunlight and in original packaging.

For more information on our bonding tapes and adhesive solutions, call us:

North America: +1 866 462 8379

Asia Pacific: +86 512 57155001

Europe: +32 (0)14 40 48 11

www.tapes.averydennison.com