TECHNICAL DATA SHEET


Avery Dennison[™] FL 545 is a single coated aluminium foil tape with a rubber based adhesive used for sealing ventilation, air conditioning systems, heat and light reflectors, joining and sealing applications and electromagnetic shielding of appliances.

FEATURES

- Dead soft aluminium foil
- Rubber based adhesive
- Easy release glassine liner

BENEFITS

- High tack and adhesion properties for average temperature applications
- Excellent resistance to moisture and plasticizers
- Medium resistance to temperature, solvents and UV light
- Fire classification: **B-s1,d0** according to the standard EN 13501-1:2018



CONSTRUCTION

Facestock: Gloss aluminum foil 50 μm **Adhesive:** Solvent rubber **Liner:** Brown glassine



Adhesive Properties		Typical Values		
THICKNESS (ASTM D3652)	US Mils	MM's	Micron's (µm)	
Liner	2.20	0.056	56	
Adhesive + Carrier	3.93	0.100	100	
Total Caliper	6.14	0.156	156	
PEEL ADHESION (ASTM D3330) 180° (12") 300 mm / min @ Room Temp				
SUBSTRATE		Lbf / in	N / Meter	
Stainless Steel	20 min dwell	4.5	790	
	24 hr dwell	5.0	870	
LOOP TACK (ASTM D6195) (12") 300 mm / min @ Room Temp				
SUBSTRATE		Lbf / in	N / Meter	
Glass		5.7	550	
STATIC SHEAR (ASTM D3654) 1" sq (6.5 cm2); 1000 g				
SUBSTRATE			Min to Fail	
Stainless Steel	eel		> 250"	
TEMPERATURES		°F	°C	
Minimum Application Temperature		50 °F	10 °C	
Minimum Service Temperature		-40 °F	-40 °C	
Maximum Service Temperature		175 °F	80 °C	

Note: The listed values are typical only and not intended to serve as product specifications

APPLICATION TECHNIQUES

- It is essential, a with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease or oil
- Bond strength is dependent upon the amount of adhesive-to-surface contact developed
- Note that different pressure, time and temperature on different (film / rigid) surface achieves different performance

STORAGE / SHELF LIFE

Two years when stored at 64-72 °F (18-22 °C) / 30-70 % relative humidity, out of direct sunlight and in original packaging.

For more information on our bonding tapes and adhesive solutions, call us:

North America: +1 866 462 8379 Asia Pacific: +86 512 57155001 Europe: +32 (0)14 40 48 11

www.tapes.averydennison.com

@2023 vMar2023, Avery Dennison Corporation. Avery Dennison and the triangle logo are registered trademarks of Avery Dennison Corporation. All rights reserved.



Performance Tapes